

For loads up to 1000kg


RIM

- A combination of a swivel castor and an adjustable lockina support
- Used to easily support and moving machines or other heavy equipment and then positioning them in a very stable manner.
- Installation starts by lowering the locking support using a nut.
- With the wheel no longer resting on the ground, the supported unit can be levelled despite any irregularities in the floor.
- Operating temperature range: -30 to +80°C

Materials

- Polyamide central control cross nut
- Anti-skid rubber mount allowing absorption of vibration and noise
- Body: Moulded cast aluminium body, hammered ivory paint finish
- Swivel system provided by 2 ball rings
- Mounting plate square
- Wheel: Black polyamide Shore D 70



















DISCOUNTS

Qty	1+	5+	14+			
Disc.	List	-5%	On request			

Part number	ØA	В	Hı	H2	L	M	ØΤ	interference ØK	Load (kg)	Price each 1 to 5
RIM42-60/PLE	42	20	71	81	55x55	42x42	6,5	84	60	46,66 €
RIM50-280/PLE	50	25	82	92	73x73	58x58	7	101	280	74,11 €
RIM63-550/PLE	63	28	103	118	90x90	70x70	9	125	550	100,71 €
RIM75-800/PLE	75	30	120	132	95x95	70x70	11	142	800	111,33 €
RIM75-1000/PLE	75	30	120	132	95x95	70x70	11	142	1000	132.76 €

Dimensions in mm

