

# Belt tensioner




## GTC

## For standard applications


- Belt tensioner for use with BTE tender arm or fixed TMR and TFR tensioners
- Integrated bearings
- Greased for life
- Materials :
  - Nut, screw and spacer : Galvanised steel
  - Roller : Polyamide
- Max working temp : 70°C



Good price/  
quality ratio



Typical application : used  
with BTE tender arm



Typical application : used  
with TFR tensioner

### DISCOUNTS

| Qty   | 1+   | 4+   | 10+        |
|-------|------|------|------------|
| Disc. | List | -10% | On request |

| Part number | A   | B   | C   | ØD | ØM  | Max speed (rpm) | Weight (kg) | Arm ref   | Stock* | Price each 1 to 3 |
|-------------|-----|-----|-----|----|-----|-----------------|-------------|-----------|--------|-------------------|
| GTC-2       | 35  | 3,0 | 51  | 30 | M8  | 8000            | 0,08        | BTE2      | ✓      | 26,87 €           |
| GTC-3/4     | 45  | 6,0 | 67  | 40 | M10 | 8000            | 0,17        | BTE3-BTE4 | ✓      | 31,65 €           |
| GTC-5       | 60  | 7,5 | 89  | 60 | M12 | 6000            | 0,40        | BTE5      | ✓      | 56,64 €           |
| GTC-6       | 90  | 9,0 | 127 | 80 | M20 | 5000            | 1,20        | BTE6-BTE7 | ✓      | 96,30 €           |
| GTC-7       | 135 | 7,0 | 169 | 90 | M20 | 4500            | 1,70        | BTE7      | -      | 189,97 €          |

\*Depending on availability - Dimensions in mm

HPC

WEB  
04/2020

www.hpceurope.com

Tél: 0 825 88 5000 Service 0,15 €/min + prix appel