


AT-type timing belt



Pitch AT5

Steel cored polyurethane

- 2nd generation metric profile
- Transmits a greater torque
- Pitch 5mm
- Working temp. -30°C to +80°C
- Max. speed 40m/s
- Efficiency: up to 98%
- Oil-resistant
- Low noise
- Resists stretching



Info.

- When ordering, add the width to the part number.
E.g.: AT5/525/25

DISCOUNTS

Qty	1+	6+	20+
Disc. List	-7%	On request	

Part number	Length	No. of teeth	Price each 1 to 5 for widths		
			10mm	16mm	25mm
AT5/225	225	45	16,78 €	24,98 €	34,15 €
AT5/255	255	51	17,21 €	25,28 €	34,38 €
AT5/280	280	56	17,42 €	25,49 €	34,67 €
AT5/300	300	60	17,62 €	25,63 €	34,91 €
AT5/330	330	66	17,72 €	25,95 €	35,54 €
AT5/340	340	68	17,75 €	26,10 €	35,54 €
AT5/375	375	75	18,07 €	26,53 €	36,33 €
AT5/390	390	78	18,17 €	26,82 €	36,68 €
AT5/420	420	84	18,44 €	27,18 €	37,23 €
AT5/450	450	90	18,77 €	27,89 €	37,84 €
AT5/455	455	91	18,85 €	28,01 €	38,10 €
AT5/500	500	100	19,80 €	29,53 €	40,96 €
AT5/525	525	105	20,73 €	31,22 €	43,36 €
AT5/545	545	109	21,34 €	32,42 €	45,36 €
AT5/600	600	120	22,86 €	34,91 €	48,53 €
AT5/610	610	122	23,20 €	35,28 €	49,32 €
AT5/660	660	132	23,83 €	36,33 €	50,91 €
AT5/710	710	142	24,98 €	37,84 €	52,92 €
AT5/720	720	144	25,19 €	38,10 €	53,32 €
AT5/750	750	150	25,49 €	38,92 €	54,10 €
AT5/780	780	156	26,26 €	40,15 €	56,09 €
AT5/825	825	165	27,08 €	41,76 €	58,09 €
AT5/860	860	172	27,73 €	42,96 €	60,11 €
AT5/975	975	195	30,07 €	46,95 €	66,09 €
AT5/1050	1050	210	32,24 €	50,13 €	70,43 €
AT5/1125	1125	225	33,51 €	52,49 €	74,42 €
AT5/1500	1500	300	40,15 €	64,07 €	92,36 €
AT5/2000	2000	400	56,09 €	86,79 €	122,64 €

Dimensions en mm

Our other products



UCF_PBT

Stainless steel/Polymer flanged bearing, Polymer and stainless steel



CPAS-H

Folding bracket, For heavy loads



PRF4590_E

Bracket for aluminium profile, PRF4590



BABPass

Hardened stainless steel ball pin with ring, With grip ring



FF10

Offset spur gear reducer, from 0.78 to 3.70 Nm



PCH

Knob for gripping, Mushroom



DOMI50

Accessories, Plate



UGH25

H Type Guide units, For Ø25 actuators



MCLred

Reducing sleeve female/female, Cylindrical - steel



PCS62K

Chain sprocket with hardened teeth, 15.875mm (DIN10B-1)



DFG

Flat suction cup, nitrile



RT25ss

Self-centering flanged locking assembly, Medium/high torque

Complementary products



GTC

Belt tensioner, For standard applications



AT5-16ECO

AT type timing pulley, Economy range - AT5 aluminium