


# AT-type timing belt



## Pitch AT5

Steel cored polyurethane

- 2<sup>nd</sup> generation metric profile
- Transmits a greater torque
- Pitch 5mm
- Working temp. -30°C to +80°C
- Max. speed 40m/s
- Efficiency: up to 98%
- Oil-resistant
- Low noise
- Resists stretching



### Info.

- When ordering, add the width to the part number.  
E.g.: AT5/525/25

### DISCOUNTS

Qty	1+	6+	20+
Disc.	List	-7%	On request

Part number	Length	No. of teeth	Price each 1 to 5 for widths		
			10mm	16mm	25mm
AT5/225	225	45	16,78 €	24,98 €	34,15 €
AT5/255	255	51	17,21 €	25,28 €	34,38 €
AT5/280	280	56	17,42 €	25,49 €	34,67 €
AT5/300	300	60	17,62 €	25,63 €	34,91 €
AT5/330	330	66	17,72 €	25,95 €	35,54 €
AT5/340	340	68	17,75 €	26,10 €	35,54 €
AT5/375	375	75	18,07 €	26,53 €	36,33 €
AT5/390	390	78	18,17 €	26,82 €	36,68 €
AT5/420	420	84	18,44 €	27,18 €	37,23 €
AT5/450	450	90	18,77 €	27,89 €	37,84 €
AT5/455	455	91	18,85 €	28,01 €	38,10 €
AT5/500	500	100	19,80 €	29,53 €	40,96 €
AT5/525	525	105	20,73 €	31,22 €	43,36 €
AT5/545	545	109	21,34 €	32,42 €	45,36 €
AT5/600	600	120	22,86 €	34,91 €	48,53 €
AT5/610	610	122	23,20 €	35,28 €	49,32 €
AT5/660	660	132	23,83 €	36,33 €	50,91 €
AT5/710	710	142	24,98 €	37,84 €	52,92 €
AT5/720	720	144	25,19 €	38,10 €	53,32 €
AT5/750	750	150	25,49 €	38,92 €	54,10 €
AT5/780	780	156	26,26 €	40,15 €	56,09 €
AT5/825	825	165	27,08 €	41,76 €	58,09 €
AT5/860	860	172	27,73 €	42,96 €	60,11 €
AT5/975	975	195	30,07 €	46,95 €	66,09 €
AT5/1050	1050	210	32,24 €	50,13 €	70,43 €
AT5/1125	1125	225	33,51 €	52,49 €	74,42 €
AT5/1500	1500	300	40,15 €	64,07 €	92,36 €
AT5/2000	2000	400	56,09 €	86,79 €	122,64 €

Dimensions en mm

## Our other products



BMF

Knurled knob - female, Knurled - blind



PV1R

Adjustable suction-cup support, Standard grip



BOXdhx

Boxed set of threaded dowel pins DIN7979D, Boxed set - extractable D...



Gal-cardan

Single universal joint eco series, Low duty



MHPGR

Arm with folding rotating handle,



EHD08-9

Internal epicyclic servo reducers, from 35 to 50 Nm



BPHF

Ball transfer unit push fit, Heavy



ACLALF

Adjustable foot for aluminium profile, Ideal for workstations



NPTF30

Spacer for tube carrier, Fixing



CRM

Moulded nylon rack, Nylon



PF30NM

Worm and wheel gear reducer, up to 8.8 Nm



T2,5-BAR

T type tooth bar stock, T2.5

## Complementary products



GTC

Belt tensioner, For standard applications



AT5-25ECO

AT type timing pulley, Economy range - AT5 aluminium