



- Materials:
  - nitrile (NBR) : black color
  - silicone (SI) : translucent
  - natural rubber (NR) : grey color

### Uses

- For moving parts with uneven surfaces




DCA05 to DCA16



DCA20 to DCA43

Natural rubber



Nitrile

Silicone

### DISCOUNTS

Qty	1+	50+	100+	150+	200+
Disc.	List	-5%	-10%	-15%	On request

Part number	ØD	H	Ød	A	Corresponding thread insert	Stock*	Price each 1 to 49
<b>Nitrile</b>							
DCA05-NBR	5,5	11,1	4	8,0	TM5M5	✓	4,67 €
DCA11-NBR	11,0	16,0	4	10,5	CTM10M5	✓	4,04 €
DCA14-NBR	13,0	15,8	4	11,0		-	4,22 €
DCA16-NBR	16,0	19,0	4	10,5		✓	4,34 €
DCA20-NBR	19,0	15,8	4	10,5		✓	4,42 €
DCA22-NBR	22,0	19,5	4	11,0	-	4,61 €	
DCA25-NBR	24,0	23,0	4	16,5	-	4,81 €	
DCA33-NBR	33,0	28,0	8	16,5	SCR30M6	-	5,00 €
DCA43-NBR	43,0	28,0	8	15,5		✓	5,32 €
<b>Silicone</b>							
DCA05-SI	5,5	11,1	4	8,0	TM5M5	-	6,19 €
DCA11-SI	11,0	16,0	4	10,5	CTM10M5	✓	5,00 €
DCA14-SI	13,0	15,8	4	11,0		-	5,40 €
DCA16-SI	16,0	19,0	4	10,5		-	5,40 €
DCA20-SI	19,0	15,8	4	10,5		✓	5,40 €
DCA22-SI	22,0	19,5	4	11,0	✓	5,40 €	
DCA25-SI	24,0	23,0	4	16,5	✓	5,60 €	
DCA33-SI	33,0	28,0	8	16,5	SCR30M6	✓	6,19 €
DCA43-SI	43,0	28,0	8	15,5		✓	6,27 €
<b>Natural rubber</b>							
DCA05-NR	5,5	11,1	4	8,0	TM5M5	-	On request
DCA11-NR	11,0	16,0	4	10,5	CTM10M5	-	4,04 €
DCA14-NR	13,0	15,8	4	11,0		-	4,22 €
DCA16-NR	16,0	19,0	4	10,5		-	4,34 €
DCA20-NR	19,0	15,8	4	10,5		✓	4,42 €
DCA22-NR	22,0	19,5	4	11,0	-	8,41 €	
DCA25-NR	24,0	23,0	4	16,5	✓	4,61 €	
DCA33-NR	33,0	28,0	8	16,5	SCR30M6	-	5,00 €
DCA43-NR	43,0	28,0	8	15,5		✓	5,70 €

\*Depending on availability - Dimensions in mm

## Our other products



BC3

Panamech, Multi-Beam stainless steel, Stainless steel - with clampin...



SLH-M

Nut for toggle clamp, Round ended nut for SLH/SLV clamp




NDS20

Double cross clamp, Parallel



DILC

Indexing plunger with cam, with cam



B

Steel bevel gear, 1:1



HRV

V-rail guidance Simple Select® system, Rail with carriage



BPL

Ball transfer unit light duty, Light



GAC

Lock for latch clamp, Strike plate




GFX

Curved tooth coupling, economy range, Steel and



MPS

Hexagonal spacer, Stainless steel 303



G0

Steel spur gear, Steel 20NCD2



PCF2

Conical flexible mount, Oval base plate

## Complementary products



TM\_CTM\_CTF

Suction cup threaded insert, Insert for suction cup - Tread click-in



SCR

Suction cup threaded insert, Insert for suction cup - Socket screw