

- **Very high deformation allows high levels of energy to be absorbed.**
- Progressive deformation
- **Materials:**
 - Core: Stainless steel plates (A2)
 - Head: Rubber
- **Hardness: NK 55-60 Shore A**
- Working temp: -40°C to +70°C


Uses

- Shock absorbing stop

Info.

- **Not sold individually, please contact us for details**
- Load and stiffness figures are given as a guide only

stainless steel




DISCOUNTS

| | | | | | |
|-------|------|------|------|------|------------|
| Qty | 1+ | 6+ | 20+ | 40+ | 100+ |
| Disc. | List | -10% | -15% | -20% | On request |

| Part number | ØG | ØD | H | T | Compression Stiffness (N/mm) | Max load (N) | Stock* | Price each 1 to 5 |
|------------------|-----|-----|----|----|------------------------------------|-----------------|--------|-------------------------|
| D-ZY4-10-10/SS | M4 | 10 | 10 | 10 | 38 | 43 | ✓ | 1,70 € |
| D-ZY4-15-8/SS | M4 | 15 | 8 | 10 | 122 | 95 | ✓ | 3,00 € |
| D-ZY4-15-10/SS | M4 | 15 | 10 | 10 | 106 | 95 | ✓ | 2,06 € |
| D-ZY4-15-15/SS | M4 | 15 | 15 | 10 | 74 | 95 | ✓ | 2,26 € |
| D-ZY6-20-15/SS | M6 | 20 | 15 | 18 | 138 | 170 | ✓ | 2,96 € |
| D-ZY6-20-20/SS | M6 | 20 | 20 | 18 | - | - | ✓ | 3,05 € |
| D-ZY6-20-25/SS | M6 | 20 | 25 | 18 | - | - | ✓ | 2,87 € |
| D-ZY6-25-10/SS | M6 | 25 | 10 | 18 | - | - | ✓ | 2,63 € |
| D-ZY6-25-15/SS | M6 | 25 | 15 | 18 | 254 | 280 | ✓ | 2,92 € |
| D-ZY6-25-20/SS | M6 | 25 | 20 | 18 | 128 | 280 | ✓ | 3,25 € |
| D-ZY6-25-25/SS | M6 | 25 | 25 | 18 | - | - | ✓ | 3,57 € |
| D-ZY6-25-30/SS | M6 | 25 | 30 | 18 | 80 | 280 | ✓ | 3,85 € |
| D-ZY8-30-20/SS | M8 | 30 | 20 | 20 | 200 | 400 | ✓ | 4,36 € |
| D-ZY8-30-25/SS | M8 | 30 | 25 | 20 | - | - | ✓ | 4,81 € |
| D-ZY8-30-30/SS | M8 | 30 | 30 | 20 | 120 | 400 | ✓ | 5,42 € |
| D-ZY8-30-40/SS | M8 | 30 | 40 | 20 | - | - | ✓ | 6,40 € |
| D-ZY8-40-20/SS | M8 | 40 | 20 | 23 | - | - | ✓ | 5,95 € |
| D-ZY8-40-30/SS | M8 | 40 | 30 | 23 | 23 | 234 | ✓ | 6,66 € |
| D-ZY8-40-40/SS | M8 | 40 | 40 | 23 | - | - | ✓ | 7,02 € |
| D-ZY10-40-30/SS | M10 | 40 | 30 | 28 | - | - | ✓ | 6,70 € |
| D-ZY10-50-20/SS | M10 | 50 | 20 | 28 | 680 | 1000 | ✓ | 9,03 € |
| D-ZY10-50-30/SS | M10 | 50 | 30 | 28 | 425 | 1000 | ✓ | 9,22 € |
| D-ZY10-50-40/SS | M10 | 50 | 40 | 28 | - | - | ✓ | 10,11 € |
| D-ZY10-50-45/SS | M10 | 50 | 45 | 28 | - | - | - | 10,81 € |
| D-ZY10-50-50/SS | M10 | 50 | 50 | 28 | - | - | ✓ | 11,89 € |
| D-ZY10-60-40/SS | M10 | 60 | 40 | 28 | - | - | - | 17,48 € |
| D-ZY10-70-45/SS | M10 | 70 | 45 | 28 | - | - | - | 22,57 € |
| D-ZY12-60-40/SS | M12 | 60 | 40 | 33 | - | - | ✓ | 17,48 € |
| D-ZY12-75-25/SS | M12 | 75 | 25 | 37 | 2000 | 2300 | ✓ | 16,61 € |
| D-ZY12-75-40/SS | M12 | 75 | 40 | 37 | 810 | 2300 | - | 24,96 € |
| D-ZY12-75-50/SS | M12 | 75 | 50 | 37 | - | - | - | 26,08 € |
| D-ZY12-75-55/SS | M12 | 75 | 55 | 37 | - | - | - | 27,31 € |
| D-ZY16-100-25/SS | M16 | 100 | 25 | 41 | - | - | - | 40,10 € |
| D-ZY16-100-50/SS | M16 | 100 | 50 | 41 | 1578 | 4200 | - | 53,22 € |
| D-ZY16-100-55/SS | M16 | 100 | 55 | 41 | 860 | 4200 | - | 55,10 € |

*Depending on availability - Dimensions in mm

Our other products



CYS
Internal circlip
DIN472, internal DIN
472



FF20
Offset spur gear
reducer, from 5.80 to
23 Nm



VELM6
Screw-on base for
hook-and-loop strip,
Polyamide



RPCtcss
Swivel castor with
central hole, Stainless
steel - Polyamide



NCT
Square tube
connector, Fixed
angle



SDA
Locking bolt support
bracket, Mounting
holes parallel to
locating bolt



BAG-MISS
Split shaft collar with
clamp lever, Stainless
steel



PRF4545_P
Stripp Aluminium
profile with
extendable slot, 45 x
45 mm



BHEX
Hexagonal cap, Black
technopolymer



ACL-PL
Joining plate for
aluminium profile,



SRP
Slotted spring pin
ISO8752, Split ISO



BCM_T
Driving collar, Driving
collar

Complementary products



DZY
Cylindrical stop, Steel



EZYSS
Stainless steel
cylindrical stop,
stainless steel