


- Suitable for most applications due to the use of self lubricating bronze bearings in the end connectors
- Allows the driving and driven elements to be mounted apart
- Obstacles can be avoided, multiple bends possible
- Position of the driven element is no longer determined by the position of the driving equipment
- Output efficiency >95%
- Dampens vibration
- Woven wire flexible shaft
- Materials:
 - Wires: blackened XC25 steel
 - Sheath: PVC



standard end
(with 2 locknuts)



Dark grey areas are fixed parts.
Light grey areas are revolving parts.

Part number	ØC core	ØM	ØA	B	ØD	E	A/F	ØF	G	ØH	J	Screw
FDSQ4-L	3,80	M15x1,0	4	10	10,5	43	22	15,0	8	12,5	4	M3
FDSQ5-L	4,75	M18x1,0	5	16	14,0	50	24	18,0	12	15,5	4	M3
FDSQ6-L	6,35	M21x1,0	6	17	17,0	59	27	21,0	14	18,5	4	M4
FDSQ8-L	8,00	M22x1,5	8	23	17,5	63	30	22,0	17	18,5	4	M4
FDSQ9-L	9,52	M26,5x1,5	10	25	22,5	69	35	26,5	20	23,0	4	M5
FDSQ13-L	12,70	M29,5x1,5	15	31	25,0	84	36	29,5	24	26,0	4	M6

Dimensions in mm

Info.

- Replace the "L" in the part number by the length required and add the desired end (R: standard; S: optional)


E.g. **FDSQ4A-500RR**

- Steel core lubricated with oil
- For continuous use, the shaft should be lubricated every 3 months
- Flexible shaft can be removed by unscrewing the knurled part. Check the sealing before re-use
- Delivered pre-bored



NOTE: For assembly, the end must be drilled and pinned to the connected shaft. The set screw is only there for positioning. It does not allow torque to be transmitted.

BEND RADIUS

$$\text{Radius} = \frac{a^2 + b^2}{4b} \text{ (mm)}$$



Depending on the sense of shaft rotation, the braiding may be different.



"L" in part number refers to length, see info.

Part number anti-clockwise	Part number bidirectional	Part number clockwise	Price for 500 mm	Price for 1000 mm	Price for 1500 mm	Price for 2000 mm	Price for 2500 mm	Price for 3000 mm
FDSQ4A-L	FDSQ4B-L	FDSQ4C-L	On request	On request	On request	On request	On request	On request
FDSQ5A-L	FDSQ5B-L	FDSQ5C-L						
FDSQ6A-L	FDSQ6B-L	FDSQ6C-L						
FDSQ8A-L	FDSQ8B-L	FDSQ8C-L						
FDSQ9A-L	FDSQ9B-L	FDSQ9C-L						
FDSQ13A-L	FDSQ13B-L	FDSQ13C-L						

Dimensions in mm

Our other products



YG3
HEAVY DUTY spur gear, Steel 35NCD6



BS3
Panamech, Multi-Beam stainless steel, Stainless steel - with set screw



INStool
Insertion tool for self tapping inserts, Insertion tool



MHQMEP
Arm with rotating handle, Square bore



ABL100000
Antistatic brush, For sensitive surfaces



RTL450
Self-centering locking assembly, High torque



SRG
Adjustable latch clamp with strike plate, Stroke from 96mm to 121,7mm



SCH
Horizontal hook toggle clamp, Horizontal Hook clamp - steel



DBC
Panamech, Multi-Beam, Aluminium -



PFL
P-FLEX Coupling, Set screw



BABT
Hardened Stainless steel ball pin,



AC156-157
Strike for toggle latch, 25.5mm

Complementary products



FDS
Flexible drive shaft, Masterflex® Steel, with PVC casing