

Thread inserts are a convenient way of repairing siezed, damaged or hanging threads. It also allows renovate threads in high quality materials.

Thread inserts can be used in varying materials such as light alloys or cast materials.

Advantages


- Quick and easy to install
- Tangs are used during installation and then serve as an anti-rotation mechanism.
- **Apart from the insertion tool, no other special tools are required.**

Assembly

- **Some tapping required**
- Refer to technical oages for assembly/disassembly instructions



Locking tang



DISCOUNTS

Qty	1+	10+	20+	30+	50+
Disc.	List	-5%	-10%	-15%	On request

Part number	Thread ØD1	Thread ØM	Length L	Assembly drill size Ø	Assembly counterbore +0,25	Assembly thread	Min thread depth	Removal drill size Ø	Removal thread depth	Price each 1 to 9
FR-M5	M5	M8	8	6,9	8,3	M8	9,5	5,5	4,0	5,20 €
FR-M6	M6	M10x1,25	10	8,8	10,3	M10x1,25	11,5	7,5	4,8	5,63 €
FR-M8	M8	M12x1,25	12	10,8	12,3	M12x1,25	13,5	9,5	4,8	6,23 €
FR-M8x100	M8x1	M12x1,25	12	10,8	12,3	M12x1,25	13,5	9,5	4,8	6,23 €
FR-M10	M10	M14x1,5	14	12,8	14,3	M14x1,5	15,5	11,5	4,8	7,73 €
FR-M10x125	M10x1,25	M14x1,5	14	12,8	14,3	M14x1,5	15,5	11,5	4,8	7,73 €
FR-M12	M12	M16x1,5	16	14,8	16,3	M16x1,5	17,5	13,5	4,8	9,98 €
FR-M12x125	M12x1,25	M16x1,5	16	14,8	16,3	M16x1,5	17,5	13,5	4,8	9,98 €

Dimensions in mm

Our other products



MDR

Dee shackle with eye bolt, Steel



BLHT20

Right angled gearbox, from 0.66 to 1.77 Nm



AT5M AT10M

AT type timing belt per metre, AT10 Steel cored polyurethane



BLH40

Right angled gearbox, from 3 to 10.30 Nm




RJA11_27

Sealing strip, Not clipping



RPCtcss

Swivel castor with central hole, Stainless steel - Polyamide - with ...



QNJ

Single row cylindrical roller bearing, Single flange on inner ring



PSG125HC

Skive hobbed spur gears - precision range, Case hardened steel 20NCD2



SSB

Stainless steel bevel gear, 1:1



BAN

Angular clamp, Universal



CHTRB

Single and dual output gearboxes, Up to 4,7 Nm



DZYSS


Stainless steel cylindrical stop, stainless steel

Complementary products



FRtool

Tool for thread repair inserts, Assembly tool



FRss

Stainless steel thread inserts, Stainless steel



INS

Self tapping steel insert, Steel



CHC

Socket headed screw, Steel class 12.19