

To be fitted to a Ø8mm axle



GAL48



- Multiple rollers mounted on one axle work as a conventional roller with two possible directions of movement
- The "Snap in" function allows you to securely and quickly position two omni-directional rollers together, and guarantees an optimised assembly
- Corrosion-resistant
- Suitable for dusty environments
- No maintenance required
- Materials:
technopolymer and stainless steel

Uses

- Control posts
- Assembly or handling stations

Info.

- Not sold individually, please contact us for details



Typical application

Allows the load to be moved in any direction

DISCOUNTS

Qty	1+	50+	100+	300+
Disc.	List	-20%	-30%	On request

Part number	ØD	X	Y	W	V	Max. load (daN)	Stock*	Price each 1 to 99
GAL48-OMNI	48	3	3	21,5	40	5	✓	8,14 €

*Depending on availability - Dimensions in mm

Our other products



CHMR90
Worm and wheel gear
reducer, up to 540
Nm



PTA50
Articulated levelling
foot, pressed base
Ø50, Ø 50



BSM
Spring plunger with
internal hexagonal
socket, steel body and
pin



CMM_SS
Male rod ends DIN
ISO12240-4, Stainless
steel / bronze -
Economy range



SLHHlok
Horizontal toggle
clamp, Horizontal
toggle clamp /
horizontal foot



BDP2R
Adjustable support
arm, Increased grip



MPS
Hexagonal spacer,
Stainless steel 303



HTD5M_15
HTD Heavy duty
timing pulley, HTD5
Steel



MPB
Hexagonal spacer,
Brass



HD
Double needle roller
universal joint, Heavy
duty



RJUM01
Closed polymer
Drylin® R bearing,
Drylin® R



MHXred
Reducing sleeve
male/female,
Hexagonal - stainless
steel

Complementary products



RLX
Free running conveyor
roller, PVC



RLXAC8
Free roller, Steel