

To be fitted to a Ø8mm axle



**GAL48**



- Multiple rollers mounted on one axle work as a conventional roller with two possible directions of movement
- The "Snap in" function allows you to securely and quickly position two omni-directional rollers together, and guarantees an optimised assembly
- Corrosion-resistant
- Suitable for dusty environments
- No maintenance required
- Materials:  
technopolymer and stainless steel

## Uses

- Control posts
- Assembly or handling stations

## Info.

- Not sold individually, please contact us for details



Typical application

**Allows the load to be moved in any direction**

## DISCOUNTS

Qty	1+	50+	100+	300+
Disc.	List	-20%	-30%	On request

Part number	ØD	X	Y	W	V	Max. load (daN)	Stock*	Price each 1 to 99
GAL48-OMNI	48	3	3	21,5	40	5	✓	8,14 €

\*Depending on availability - Dimensions in mm

## Our other products



RBGpl  
Swivel castor with plate, Steel - grey rubber



RFVcap  
Stainless steel protective cover, Closed protective cover



DOMI120  
Accessories, Clamping lever



RURt  
Swivel castor with central hole, Polyurethane - Aluminium rim (Free



CSS  
Spherical bushing, Steel / self lubricating steel



SEH  
Horizontal stirrup toggle clamp, Horizontal stirrup clamp - steel



GEC  
Rubber latch clamp with strike plate, Lockable



ACLEPP  
Right angled bracket for aluminium profile, 4 holes



PR125  
Articulated foot Ø123, Ø 123



MFB\_MHB  
Moulded plastic bevel gear (nylon), 4:1



T39\_T49  
Extension spring in metre length steel, by



MDB\_MTB  
Moulded plastic bevel gear (nylon), 2:1

## Complementary products



RLX  
Free running conveyor roller, PVC



RLXAC8  
Free roller, Steel