

To be fitted to a Ø8mm axle



GAL48

- Multiple rollers mounted on one axle work as a conventional roller with two possible directions of movement
- The "Snap in" function allows you to securely and quickly position two omni-directional rollers together, and guarantees an optimised assembly
- Corrosion-resistant
- Suitable for dusty environments
- No maintenance required
- Materials: technopolymer and stainless steel





### Uses

- Control posts
- Assembly or handling stations

### Info.

- Not sold individually, please contact us for details



Typical application

Allows the load to be moved in any direction

### DISCOUNTS

Qty	1+	50+	100+	300+
Disc.	List	-20%	-30%	On request

Part number	ØD	X	Y	W	V	Max. load (daN)	Stock*	Price each 1 to 99
GAL48-OMNI	48	3	3	21,5	40	5	✓	8,14 €

\*Depending on availability - Dimensions in mm

## Our other products



PSG1

Spur gear - precision range, Pre-hardened Steel 35NCD6



DPAR\_DKON

Progressive stop, Steel



SH0

Parallel axis helical gear, Steel 20NCD2



NT121

Spur gear coaxial gearbox, from 20 to 68 Nm - In-line



EBC

Cap nut Hygienic Design®, Compact



BPMc

Stainless steel slotted spring plunger with ceramic ball tip, 303 St...



BH01

Single housed bearing, Bearing fitted with adhesive



ADSR

Backlash free coupling Gerwah®, from 12.5 to 525Nm




BOXKK

Boxed set of DIN6885A keys, Boxed set - Steel or stainless steel



RURt

Swivel castor with central hole, Polyurethane - Aluminium rim (Free



IN1

Internal gear, Machined plastic (delrin)



CHMX\_CHMDX

Shaft for worm and wheel reducer CHMR and CHM, CHMR and CHM gearbox...

## Complementary products



RLX

Free running conveyor roller, PVC



RLXAC8

Free roller, Steel