

To be fitted to a Ø8mm axle



GAL48

- Multiple rollers mounted on one axle work as a conventional roller with two possible directions of movement
- The "Snap in" function allows you to securely and quickly position two omni-directional rollers together, and guarantees an optimised assembly
- Corrosion-resistant
- Suitable for dusty environments
- No maintenance required
- Materials: technopolymer and stainless steel





### Uses

- Control posts
- Assembly or handling stations

### Info.

- Not sold individually, please contact us for details



Typical application

Allows the load to be moved in any direction

### DISCOUNTS

Qty	1+	50+	100+	300+
Disc.	List	-20%	-30%	On request

Part number	ØD	X	Y	W	V	Max. load (daN)	Stock*	Price each 1 to 99
GAL48-OMNI	48	3	3	21,5	40	5	✓	8,14 €

\*Depending on availability - Dimensions in mm

## Our other products



AT5courroie

AT type timing belt,  
AT5 Steel cored  
polyurethane




BL8

Right angled gearbox,  
from 0.20 to 2 Nm



FF50

Offset spur gear  
reducer, from 111 to  
425 Nm



CHB

Worm and wheel gear  
reducer, up to 41 Nm




GMK17\_BR

Clamp for guiding  
profile, Rounded only  
- double



GP

Spring loaded toggle  
latch, Standard




EPRF

High helix leadscrew,  
Flanged nut - up to  
40mm per rotation



GG1

Ground spur gear,  
Heat treated steel



MLY

Bow shackle with eye  
bolt, Steel




BOXKK

Boxed set of  
DIN6885A keys,  
Boxed set - Steel or



CHM63-MOT

Asynchronous AC  
motorgearboxes 0.37  
to 1.5kW, 0.37 to



M1

Worm and wheel set,  
Machined plastic  
(delrin)

## Complementary products



RLX

Free running conveyor  
roller, PVC



RLXAC8

Free roller, Steel