


Module 0,5

Brass CuZn39Pb3

NEW!




- Spur gear with JIS grade 8teeth (JISB1702-1:1998)
- Pressure angle 20°
- Material:
Brass CuZn39Pb3 (C6304)



Info

- *Torque (bending strength)



DISCOUNTS

Qty	1+	6+	10+
Disc.	Price	-12%	On request

Part number	Teeth Z	ØP	ØD	ØM	ØA (H7)	E	F	G	ØT	J	Torque* (Nm)	Weight (kg)	Price
													each 1 to 5
GB0.5-15-RA03T	15	7,5	8,5	8,5	3	3	11	14	M3	2,5	0,058	0,005	10,35 €
GB0.5-16-RA03T	16	8,0	9,0	9,0	3	3	11	14	M3	2,5	0,065	0,006	10,35 €
GB0.5-20-RA04	20	10,0	11,0	8,5	4	3	7	10	-	-	0,091	0,004	10,97 €
GB0.5-20-RA03T	20	10,0	11,0	11,0	3	3	11	14	M3	2,5	0,091	0,010	12,01 €
GB0.5-22-RA03T	22	11,0	12,0	9,0	3	3	7	10	M3	3,5	0,10	0,005	12,79 €
GB0.5-24-RA04T	24	12,0	13,0	10,0	4	3	7	10	M3	3,5	0,12	0,006	13,42 €
GB0.5-25-RA04	25	12,5	13,5	11,0	4	3	7	10	-	-	0,12	0,008	13,42 €
GB0.5-30-RA04	30	15,0	16,0	13,0	4	3	7	10	-	-	0,16	0,011	14,85 €
GB0.5-30-RA03T	30	15,0	16,0	12,0	3	3	7	10	M3	3,5	0,16	0,010	15,65 €
GB0.5-30-RA04T	30	15,0	16,0	12,0	4	3	7	10	M3	3,5	0,16	0,010	15,65 €
GB0.5-30-RA05T	30	15,0	16,0	12,0	5	3	7	10	M4	3,5	0,16	0,009	15,65 €
GB0.5-38-RA04T	38	19,0	20,0	16,0	4	3	7	10	M3	3,5	0,22	0,018	19,32 €
GB0.5-40-RA04	40	20,0	21,0	17,0	4	3	7	10	-	-	0,23	0,020	18,49 €
GB0.5-50-RA04T	50	25,0	26,0	22,0	4	3	7	10	M3	3,5	0,31	0,033	23,61 €

Dimensions in mm


Module

Brass CuZn39Pb3

0,8



NEW!



- Spur gear with JIS grade 8teeth (JISB1702-1:1998)


- Pressure angle 20°

- Material:

Brass CuZn39Pb3 (C6304)

Info

- *Torque (bending strength)



DISCOUNTS

Qty	1+	6+	10+
Disc.	Price	-12%	On request

Part number	Teeth Z	ØP	ØD	ØM	ØA (H7)	E	F	G	ØT	J	Torque* (Nm)	Weight (kg)	Price
													each 1 to 5
GB0.8-15-RA04T	15	12,0	13,6	9,0	4	4	8	12	M3	4	0,20	0,007	13,42 €
GB0.8-16-RA04T	16	12,8	14,4	10,0	4	4	8	12	M3	4	0,22	0,008	14,04 €
GB0.8-20-RA05	20	16,0	17,6	13,5	5	4	8	12	-	-	0,31	0,014	15,26 €
GB0.8-20-RA04T	20	16,0	17,6	12,0	4	4	8	12	M3	4	0,31	0,013	16,67 €
GB0.8-24-RA05T	24	19,2	20,8	16,0	5	4	8	12	M4	4	0,40	0,021	21,76 €
GB0.8-25-RA05	25	20,0	21,6	17,0	5	4	8	12	-	-	0,43	0,024	20,36 €
GB0.8-30-RA04T	30	24,0	25,6	20,0	4	4	8	12	M3	4	0,55	0,035	23,40 €
GB0.8-30-RA05	30	24,0	25,6	20,0	5	4	8	12	-	-	0,55	0,034	22,39 €
GB0.8-40-RA05	40	32,0	33,6	20,0	5	4	8	12	-	-	0,79	0,046	27,04 €

Dimensions in mm

Module


Brass CuZn39Pb3

1,0




- Spur gear with JIS grade 8teeth (JISB1702-1:1998)
- Pressure angle 20°
- Material:
Brass CuZn39Pb3 (C6304)

NEW!



Info

- *Torque (bending strength)



DISCOUNTS

Qty	1+	6+	10+
Disc. Price	-12%	On request	

Part number	Teeth		ØA				Torque*		Weight		Price each		
	Z	ØP	ØD	ØM	(H7)	E	F	G	ØT	J	(Nm)	(kg)	1 to 5
GB1-16-RA05T	16	16	18	12	5	6	8	14	M4	4	0,52	0,015	17,71 €
GB1-18-RA06T	18	18	20	15	6	6	8	14	M4	4	0,62	0,021	19,94 €
GB1-20-RA06T	20	20	22	16	6	6	8	14	M4	4	0,73	0,026	20,72 €
GB1-22-RA06T	22	22	24	18	6	6	8	14	M4	4	0,83	0,033	22,78 €
GB1-24-RA06T	24	24	26	20	6	6	8	14	M4	4	0,94	0,040	23,19 €
GB1-30-RA06T	30	30	32	25	6	6	8	14	M4	4	1,28	0,065	28,08 €
GB1-40-RA06T	40	40	42	28	6	6	8	14	M4	4	1,86	0,100	47,40 €

Dimensions in mm

Our other products



PRF_FIX_ANG

Fastener for aluminium profile, Angular joint



PRF_PL_4590

Joining plate for aluminium profile, Joint plate - 45x90 mm



G0

Steel spur gear, Steel 20NCD2



R203

Die spring ISO10243, Light




RFVfp

Stainless steel worm and wheel gearboxes, Mounting bracket



NK27

Drylin@N miniature guiding system, Width 27 mm



H1

Crossed helical gear crossed axis at 90°, Machined plastic (delrin)



RJA10_03

Sealing strip, Clipping



ACM_DZ

Clip for bonnet fastener, Clip



GPB

Threaded spherical knob, Moulded thread



BDP1R

Adjustable support arm, Single clamp



BLHB40

Right angled gearbox, bored shafts, up to 10.3 Nm

Complementary products



YG0

HEAVY DUTY spur gear, Steel 35NCD6



G0

Steel spur gear, Steel 20NCD2



ZG0

Plastic spur gear, Machined plastic (delrin)