
Module 0,5


Brass CuZn39Pb3



- ***Spur gear with JIS grade 8teeth (JISB1702-1:1998)***
- *Pressure angle 20°*
- *Material:*
  Brass CuZn39Pb3 (C6304)

Info

- **Torque (bending strength)*



DISCOUNTS


Qty	1+	6+	10+
Disc.	Price	-12%	On request

Part number	Teeth Z	ØP	ØD	ØM	ØA (H7)	E	F	G	ØT	J	Torque* (Nm)	Weight (kg)	Price each 1 to 5
GB0.5-15-RA03T	15	7,5	8,5	8,5	3	3	11	14	M3	2,5	0,058	0,005	27,45 €
GB0.5-16-RA03T	16	8,0	9,0	9,0	3	3	11	14	M3	2,5	0,065	0,006	27,45 €
GB0.5-20-RA04	20	10,0	11,0	8,5	4	3	7	10	-	-	0,091	0,004	27,98 €
GB0.5-20-RA03T	20	10,0	11,0	11,0	3	3	11	14	M3	2,5	0,091	0,010	31,86 €
GB0.5-22-RA03T	22	11,0	12,0	9,0	3	3	7	10	M3	3,5	0,10	0,005	33,93 €
GB0.5-24-RA04T	24	12,0	13,0	10,0	4	3	7	10	M3	3,5	0,12	0,006	35,58 €
GB0.5-25-RA04	25	12,5	13,5	11,0	4	3	7	10	-	-	0,12	0,008	35,58 €
GB0.5-30-RA04	30	15,0	16,0	13,0	4	3	7	10	-	-	0,16	0,011	36,35 €
GB0.5-30-RA03T	30	15,0	16,0	12,0	3	3	7	10	M3	3,5	0,16	0,010	39,92 €
GB0.5-30-RA04T	30	15,0	16,0	12,0	4	3	7	10	M3	3,5	0,16	0,010	39,92 €
GB0.5-30-RA05T	30	15,0	16,0	12,0	5	3	7	10	M4	3,5	0,16	0,009	39,92 €
GB0.5-38-RA04T	38	19,0	20,0	16,0	4	3	7	10	M3	3,5	0,22	0,018	41,38 €
GB0.5-40-RA04	40	20,0	21,0	17,0	4	3	7	10	-	-	0,23	0,020	41,49 €
GB0.5-50-RA04T	50	25,0	26,0	22,0	4	3	7	10	M3	3,5	0,31	0,033	45,76 €

Dimensions in mm

Brass CuZn39Pb3


Module 0,8



- ***Spur gear with JIS grade 8teeth (JISB1702-1:1998)***
- *Pressure angle 20°*
- *Material:*
  Brass CuZn39Pb3 (C6304)

Info

- **Torque (bending strength)*



DISCOUNTS


Qty	1+	6+	10+
Disc.	Price	-12%	On request

Part number	Teeth Z	ØP	ØD	ØM	ØA (H7)	E	F	G	ØT	J	Torque* (Nm)	Weight (kg)	Price each 1 to 5
GB0.8-15-RA04T	15	12,0	13,6	9,0	4	4	8	12	M3	4	0,20	0,007	On request
GB0.8-16-RA04T	16	12,8	14,4	10,0	4	4	8	12	M3	4	0,22	0,008	On request
GB0.8-20-RA05	20	16,0	17,6	13,5	5	4	8	12	-	-	0,31	0,014	30,36 €
GB0.8-20-RA04T	20	16,0	17,6	12,0	4	4	8	12	M3	4	0,31	0,013	On request
GB0.8-24-RA05T	24	19,2	20,8	16,0	5	4	8	12	M4	4	0,40	0,021	37,74 €
GB0.8-25-RA05	25	20,0	21,6	17,0	5	4	8	12	-	-	0,43	0,024	37,38 €
GB0.8-30-RA04T	30	24,0	25,6	20,0	4	4	8	12	M3	4	0,55	0,035	45,35 €
GB0.8-30-RA05	30	24,0	25,6	20,0	5	4	8	12	-	-	0,55	0,034	43,39 €
GB0.8-40-RA05	40	32,0	33,6	20,0	5	4	8	12	-	-	0,79	0,046	55,17 €

Dimensions in mm

Brass CuZn39Pb3


Module 1,0



- ***Spur gear with JIS grade 8teeth (JISB1702-1:1998)***
- *Pressure angle 20°*
- *Material:*
  Brass CuZn39Pb3 (C6304)

Info

- **Torque (bending strength)*



DISCOUNTS

Qty	1+	6+	10+
Disc.	Price	-12%	On request

Part number	Teeth Z	ØP	ØD	ØM	ØA (H7)	E	F	G	ØT	J	Torque* (Nm)	Weight (kg)	Price each 1 to 5
GB1-16-RA05T	16	16	18	12	5	6	8	14	M4	4	0,52	0,015	43,35 €
GB1-18-RA06T	18	18	20	15	6	6	8	14	M4	4	0,62	0,021	44,75 €
GB1-20-RA06T	20	20	22	16	6	6	8	14	M4	4	0,73	0,026	46,50 €
GB1-22-RA06T	22	22	24	18	6	6	8	14	M4	4	0,83	0,033	30,20 €
GB1-24-RA06T	24	24	26	20	6	6	8	14	M4	4	0,94	0,040	30,75 €
GB1-30-RA06T	30	30	32	25	6	6	8	14	M4	4	1,28	0,065	63,01 €
GB1-40-RA06T	40	40	42	28	6	6	8	14	M4	4	1,86	0,100	91,87 €

Dimensions in mm

Our other products


CCA


Angular miter gear 60°, 1,5 to 3


RHTplss

High Temperature Castor, up to 200kg


GMK17_BR

Clamp for guiding profile, Rounded only - single


TR

Spur round rack, Stainless steel - module 0,25-1,5


CDPC

Flanged drill bushing, Steel


PW_PWG1


Wheel - precision range, Bronze


CHAR7530

Spring hinge, welded


M0

Worm, Unhardened steel


RPPM

RPP type belt per metre, RPP8 Steel cored polyurethane


DILC

Indexing plunger with cam, with cam


MHMEP

Arm with rotating handle, Prebored


UCP_PBT

Stainless/Polymer pillow block bearing, Polymer and stainless steel

Complementary products


G0

Steel spur gear, Steel 20NCD2


SSG0

Stainless steel spur gear, Stainless steel 304L


ZG0

Plastic spur gear, Machined plastic (delrin)