

Right angle gearbox

HLA19

Torque up to 43 Nm



- **Right angle bevel gearbox**
- Max speed 1,400 rpm
- Output backlash: 12' to 20'
- Materials:
 - Components: steel
 - Case: cast iron
- Thermal power: 4.5 kW (Heat dissipation capability)

Part number

- When ordering, specify the rotation direction and mounting position by replacing **E** and **B3** in the Part number (see presentation page)





Hollow output shaft C



Single output shaft S or dual shafts B

With input shaft



DISCOUNTS

Qty	1+	2+	4+
Disc.	List	-5%	On request

Part number	Ratio	Ø input shaft (h6)	Output shaft	Max output speed (rpm)	Mechanical output torque (Nm)	Weight (kg)	Price each
HLA19-1-C-E-B3	1:1	19	hollow	1400	35	8,5	384,17 €
HLA19-2-C-E-B3	2:1	14	hollow	700	40	8,5	384,17 €
HLA19-3-C-E-B3	3:1	14	hollow	467	43	8,5	384,17 €
HLA19-1-S-E-B3	1:1	19	single	1400	35	8,5	382,92 €
HLA19-2-S-E-B3	2:1	14	single	700	40	8,5	382,92 €
HLA19-3-S-E-B3	3:1	14	single	467	43	8,5	382,92 €
HLA19-1-B-E-B3	1:1	19	dual	1400	35	8,5	395,43 €
HLA19-2-B-E-B3	2:1	14	dual	700	40	8,5	395,43 €
HLA19-3-B-E-B3	3:1	14	dual	467	43	8,5	395,43 €

*For maximum torque and a service factor applied, see presentation page - Dimensions en mm

Our other products



DOMI_MD
Domino rotary table,
55/1



CHML40
Worm and wheel gear
reducer, up to 57 Nm
- Integrated torque
limiter



KBS_UU
Stainless steel closed
precision linear
bearing, Precision -
stainle...



WINGbr
Wing screw, hand
tightened DIN316,
Brass DIN 316



PRF_ART
Articulated bracket for
use with aluminium
profile, Standard



ACL-PL
Joining plate for
aluminium profile,
Joint plate - 176x86
mm



AT5M AT10M
AT type timing belt
per metre, AT5 Steel
cored polyurethane




DCA
Suction cup, 1.5
bellows, nitrile



VTHA
Magnetic screw with
hexagonal head, Steel



CHA35
Hinge for aluminium
profile, Hinge



PRF-SCREEN-1
Screen support, Basic
support



EMS
Stainless steel knurled
thumb nut, Knurled

Complementary products



HLC19
Right angle spiro
bevel gearbox, Up to
43Nm



HLA24
Right angle spiro
bevel gearbox, Up to
78Nm