


- **Compact cylindrical bearing**
- With integrated seals
- Material:
 - Housing: Pressed sheet steel
 - Balls: Steel 70 HRC +/-2
- Only for linear movement (not rotation)



Part number	normal backlash		reduced backlash	
	bore	shaft	bore	shaft
Steel or cast iron housing	H7	h6	H6	j7
Light alloy housing	K7	h6	K6	j5

DISCOUNTS

Qty	1+	5+	10+	25+
Disc. List	-6%	-12%	On request	

Part number	Ød (mm)	OD (mm)	L (mm)	Weight (g)	Loads		Stock*	Price each 1 to 4
					Dynamic Cr (N)	Static Co (N)		
KH12-28-LL	12	19	28	18,5	605	495	✓	14,05 €
KH14-28-LL	14	21	28	20,5	600	505	✓	14,34 €
KH16-30-LL	16	24	30	27,5	775	600	✓	16,29 €
KH20-30-LL	20	28	30	32,5	1050	880	✓	14,73 €
KH25-40-LL	25	35	40	66,0	1830	1560	✓	18,03 €
KH30-50-LL	30	40	50	95,0	2700	2450	✓	25,29 €
KH40-60-LL	40	52	60	182,0	4250	4000	✓	42,92 €
KH50-70-LL	50	62	70	252,0	5300	5700	-	60,00 €

*Depending on availability - Dimensions in mm

Our other products



ACLCHARJ

Hinge for aluminium profile, Adjusts in 2 directions



B_ECO

Eco. range steel bevel gear, 1:1



ERF

Quick fitting threaded cable terminal, Cable terminal with threaded ...



CHA1056-U4

Screwed hinge, 180°



BSM

Spring plunger with internal hexagonal socket, steel body, plastic pin



CHV

Mechanical speed variator, from 0,18 to 1,5kW



METEB

Self-lubricating blanks, Bronze BP25



DOM150

Accessories, Clamping lever



METC

Flanged sintered bronze bush, Self-lubricating sintered bronze



NAST

Cam follower without axial guide, With interior ring



MBF

Threaded blocking clamp, Threaded locking clamp



MSP3815

Masterplate® glueable insert rectangular, rectangular with nut

Complementary products



ZA

Shaft for linear guides, Hardened ground steel



FGWA

End support, With base