


- **Compact cylindrical bearing**
- With integrated seals
- **Material:**
  - Housing: Pressed sheet steel
  - Balls: Steel 70 HRC +/-2
- Only for linear movement (not rotation)



Part number	normal backlash		reduced backlash	
	bore	shaft	bore	shaft
Steel or cast iron housing	H7	h6	H6	j7
Light alloy housing	K7	h6	K6	j5

### DISCOUNTS

Qty	1+	5+	10+	25+
Disc. List	-6%	-12%	On request	

Part number	Ød (mm)	OD (mm)	L (mm)	Weight (g)	Loads		Stock*	Price each 1 to 4
					Dynamic Cr (N)	Static Co (N)		
KH12-28-LL	12	19	28	18,5	605	495	✓	14,05 €
KH14-28-LL	14	21	28	20,5	600	505	✓	14,34 €
KH16-30-LL	16	24	30	27,5	775	600	✓	16,29 €
KH20-30-LL	20	28	30	32,5	1050	880	✓	14,73 €
KH25-40-LL	25	35	40	66,0	1830	1560	✓	18,03 €
KH30-50-LL	30	40	50	95,0	2700	2450	✓	25,29 €
KH40-60-LL	40	52	60	182,0	4250	4000	✓	42,92 €
KH50-70-LL	50	62	70	252,0	5300	5700	-	60,00 €

\*Depending on availability - Dimensions in mm

## Our other products



MBF

Threaded blocking clamp, Threaded locking clamp



RBNpl

Fixed castor with plate, Steel - rubber



HRV

V-rail guidance Simple Select® system, Rail with carriage



APB\_T

Adjusting rod for clamp - Female, Bored



PVL

Small lobed handle, Polyamide



CLG3

Moulded plastic spur gear, Moulded plastic (nylon)



BLHM50

Right angled gearbox, double output shafts, up to 30 Nm




AT10-50ECO

AT type timing pulley, Economy range - AT10 aluminium



CHMR63

Worm and wheel gear reducer, up to 196 Nm



KGS

Ball screw, supplied by the metre, Rolled ball screw, per metre



TSRTC

Stem support for castor, For swivel castor with central



PSG08

Spur gear - precision range, Pre-hardened Steel 35NCD6

## Complementary products



ZA

Shaft for linear guides, Hardened ground steel



FGWA

End support, With base