

Articulated foot with sheet metal base Ø100

PAMF100

Max load: 15,000N
Rubber sole in EPDM, blue



- **Articulated adjustable levelling feet**
- Axial articulation +/- 10°
- With non-slip sole in EPDM Blue
- Stainless steel in shiny finish
- Materials:
 - Base: shiny 304 stainless steel sheet
 - Thread: 304 stainless steel, supplied without nut
 - Sole: EPDM blue

Options

- Other thread dimensions on request
- 316 grade Stainless steel on request

Advantages

- Hygienic special pad for easy cleaning.
- Food processing, Pharmaceutical and Chemical Environment



DISCOUNTS

| | | | | | |
|-------------|-----|------|------|------|------------|
| Qty | 1+ | 6+ | 10+ | 15+ | 20+ |
| Disc. Price | -5% | -10% | -10% | -15% | On request |

| References | Threading | | B | A | A/F | G | H | Static load(N) | Price per unit 1 to 5 |
|-------------------|-----------|-----|-----|------|-----|----|-------|----------------|-----------------------|
| | ØD | ØF | | | | | | | |
| PAMF100-16-100/EB | 100 | M16 | 100 | 39.5 | 13 | 30 | 139.5 | 15000 | 53,37€ |
| PAMF100-16-150/EB | 100 | M16 | 150 | 39.5 | 13 | 30 | 189.5 | 15000 | 54,99€ |
| PAMF100-16-200/EB | 100 | M16 | 200 | 39.5 | 13 | 30 | 239.5 | 15000 | 58,69€ |
| PAMF100-20-100/EB | 100 | M20 | 100 | 43.0 | 17 | 30 | 143.0 | 15000 | 56,55€ |
| PAMF100-20-150/EB | 100 | M20 | 150 | 43.0 | 17 | 30 | 193.0 | 15000 | 59,76€ |
| PAMF100-20-200/EB | 100 | M20 | 200 | 43.0 | 17 | 30 | 243.0 | 15000 | 63,46€ |

* Depending on availability - Dimensions in mm

Our other products



TK
Topball self-aligning linear bearing, Topball self-aligning



AC
Strike for toggle latch, 13mm



MPS
Hexagonal spacer, Stainless steel 303



MPE
Hexagonal spacer, Steel



RMSA
Adjustable shock-absorber, Adjustable



VTLF
3 lobed handle, Polyamide - Brass



ACLLPP
Latch for aluminium profile, Spring operated latch



HCA
Magnetic screw with socket, Steel



SA_SAKH
Housing for linear bearing, Closed - light load



CHMX_CHMDX
Shaft for worm and wheel reducer CHMR and CHM, CHMR and CHM



CHAu
Screwed hinge, 270°



MCL
Cylindrical threaded sleeve, Cylindrical - stainless steel

Complementary products



PTA50ssEB
Articulated foot with sheet metal base
Ø50, Articulated foot



PTA80ssEB
Articulated foot with sheet metal base
Ø80, Articulated foot



PTA100ssEB
Articulated foot with sheet metal base
Ø100, Articulated foot



PAMF80EB
Articulated foot with sheet metal base
Ø80, Articulated foot