

Articulated foot with sheet metal base Ø100

PAMF100

Max load: 15,000N
Rubber sole in EPDM, blue



- **Articulated adjustable levelling feet**
- Axial articulation +/- 10°
- With non-slip sole in EPDM Blue
- Stainless steel in shiny finish
- Materials:
 - Base: shiny 304 stainless steel sheet
 - Thread: 304 stainless steel, supplied without nut
 - Sole: EPDM blue

Options

- Other thread dimensions on request
- 316 grade Stainless steel on request

Advantages

- Hygienic special pad for easy cleaning.
- Food processing, Pharmaceutical and Chemical Environment



DISCOUNTS

Qty	1+	6+	10+	15+	20+
Disc. Price	-5%	-10%	-15%	On request	

References	Threading		B	A	A/F	G	H	Static load(N)	Price per unit 1 to 5
	ØD	ØF							
PAMF100-16-100/EB	100	M16	100	39.5	13	30	139.5	15000	53,37€
PAMF100-16-150/EB	100	M16	150	39.5	13	30	189.5	15000	54,99€
PAMF100-16-200/EB	100	M16	200	39.5	13	30	239.5	15000	58,69€
PAMF100-20-100/EB	100	M20	100	43.0	17	30	143.0	15000	56,55€
PAMF100-20-150/EB	100	M20	150	43.0	17	30	193.0	15000	59,76€
PAMF100-20-200/EB	100	M20	200	43.0	17	30	243.0	15000	63,46€

* Depending on availability - Dimensions in mm

Our other products



VHTM

Hexagonal headed screw Hygienic Design®, Stainless steel



PCS375S

Chain sprocket - Stainless steel, 9.525 (DIN 06B-1)



TBD

Manual leadscrew table with opposing threads, 40kg



MSP3815

Masterplate® glueable insert rectangular, rectangular with



G0

Steel spur gear, Steel 20NCD2



GLB

Small 6 lobe female handle, Technopolymer - Stainless steel



GG2

Ground spur gear, Heat treated steel




ES

Simple support base (bipod), Plastic



DOMI80

Accessories, Clamping lever



KB_OP

Open precision linear bearing, Precision -



RURt

Swivel castor with central hole,



PRF3232

Standard aluminium profile, 32 x 32 mm

Complementary products



PTA50ssEB

Articulated foot with sheet metal base Ø50, 4 000N



PTA80ssEB

Articulated foot with sheet metal base Ø80, 10000N



PTA100ssEB

Articulated foot with sheet metal base Ø100, 15000N



PAMF80EB

Articulated foot with sheet metal base Ø80, Articulated foot