Clamp lever with threaded insert [88]

With thread insert







PCLA_M PCI AMSS

- Control lever with threaded insert

- Materials:

Insert: steel (class 5.8) or stainless steel (303) Handle: glass fibre reinforced polyamide plastic Mechanism: splined diecast zinc

- Finish: Blackened steel
- Color · black

Uses

- The lever is normally in a locked position
- Raise the handle to release the lever and turn to required position
- When handle is released, lever will automatically lock in new position

- H4 = clearance height required for handle



Part	Thread						
number	X	T	ØD	ØD1	Н	H1	H2
PCLA01M4	M4	9	10,0	13,0	24,5	4,0	15,0
PCLA01M5	M5	9	10,0	13,0	24,5	4,0	15,0
PCLA01M6	M6	9	10,0	13,0	24,5	4,0	15,0
PCLA02M6	M6	12	13,5	18,0	28,5	6,5	17,5
PCLA02M8	M8	12	13,5	18,0	28,5	6,5	17,5
PCLA03M8	M8	14	16,0	21,5	37,0	10,0	24,0
PCLA03M10	M10	14	16,0	21,5	37,0	10,0	24,0
PCLA04M10	M10	17	19,0	25,5	43,0	10,0	26,0
PCLA04M12	M12	17	19,0	25,5	43,0	10,0	26,0
PCLA05M12	M12	23	23,0	30,0	49,0	12,0	33,0
PCLA05M16	M16	23	23.0	30.0	49.0	12.0	33.0

Part n	umber		Stock*						
Steel	Stainless	Н3	H4	Α	A1	В	Steel	StS	Steel Stainless
PCLA01M4	-	30,0	33,5	40	47,0	7,5	~	-	7,50 € -
PCLA01M5	PCLA01M5SS	30,0	33,5	40	47,0	7,5	~	-	8,07 € 12,64 €
PCLA01M6	PCLA01M6SS	30,0	33,5	40	47,0	7,5	V	-	8,07 € 12,64 €
PCLA02M6	PCLA02M6SS	41,5	45,5	65	75,0	9,5	V	_	9,59 € 14,87 €
PCLA02M8	PCLA02M8SS	41,5	45,5	65	75,0	9,5	~	~	9,59 € 14,87 €
PCLA03M8	PCLA03M8SS	53,5	58,0	80	91,5	11,0	V	V	11,77 € 18,30 €
PCLA03M10	PCLA03M10SS	53,5	58,0	80	91,5	11,0	V	-	11,77 € 18,30 €
	PCLA04M10SS		66,0	95	109,0	13,0	~	-	15,01 € 26,45 €
PCLA04M12	PCLA04M12SS	61,0	66,0	95	109,0	13,0	V	-	15,01 € 26,45 €
PCLA05M12	PCLA05M12SS	72,0	77,0	110	126,0	15,5	V	-	18,15 € 31,89 €
PCLA05M16	PCLA05M16SS	72,0	77,0	110	126,0	15,5	~	-	18,15 € 31,89 €
*Depending	on availability -	Dimon	eione in	mm					

^{*}Depending on availability - Dimensions in mm





Our other products



Roll-Ring® chain tensioner, Roll-Ring® Self-adjusting



BoWex® curved tooth gear coupling, Nylon and steel



Accessories, Turntable



Shaft clamp with keyway. Set screw



Swivel castor with double brake, Polyurethane -Aluminium rim (Free



Indexing plunger mini, miniature



Miniature motorised actuator 2A, 2 ampers



Right angle spiro bevel gearbox, Up to 78Nm



Stainless steel bevel gear, 1:1



Handle for aluminium profile, Ergonomic



Spherical bushing, Steel / self lubricating



Ball lock pins lockable , Stainless steel

Complementary products



Die cast zinc clamping lever - female, Zamak



Stainless steel indexing handle female, Stainless steel



Technopolymer clamping lever - male, Plastic



Die cast zinc clamping lever - male, Zamak