Mounting feet with integrated castors

Offset castor

PDR

- ***Combines the advantages of a static mounting foot and a castor***
- *Use a hexagonal spanner to release the castor*
- *Castor protrudes 12.5mm when released*
- *Only for use on surfaces that are smooth (crevices less than 5mm) and horizontal (max slope 3°)*
- *Max static load 2,500 kg per foot*
- *Max load 200 kg per foot if used in movable mode*
- *Materials:*
  Base - Polyamide
  Sole - NBR rubber
  Threaded shaft - Chromed steel




Typical application


- *A vessel remains static whilst the product within is processed but once empty, can be moved for cleaning purposes.*

Advantages

- *Flexibility (1 item performs 2 functions)*
- *Less manœuvring to move a structure*
- *Time saving*



Retracting the castor



DISCOUNTS

Qty	1+	6+	10+
Disc.	List	-5%	On request

Part number	ØM	L	Load Castor fixed (static) (kg)	Load Castor free (dynamic) (kg)	Price each 1 to 5
With threaded shaft					
PDR100-16-50/RD	M16	50	2500	200	118,60 €
PDR100-16-100/RD	M16	100	2500	200	122,18 €
PDR100-20-75/RD	M20	75	2500	200	122,18 €
PDR100-20-125/RD	M20	125	2500	200	125,78 €
PDR100-24-75/RD	M24	75	2500	200	122,18 €
PDR100-24-125/RD	M24	125	2500	200	125,78 €
With 80x80mm mounting plate					
PDR100-80-80/RD	4x8.5mm holes		2500	200	122,18 €

Dimensions in mm

Our other products



Fixed levelling foot, Flanged plate



Speed controller 5A accessories, USB cable for PC link



Slat top chain stainless steel, Large range 805



Eco range Spur gear, Steel C45




Stainless steel bevel gear, 1:1



Right angled support clamp, Right angled support clamp



Hexagonal headed screw VTH - DIN933, Brass



Torsion spring, Stainless steel




Brush, stainless steel



Chain tool, Drive chain maintenance



Motor-gearbox 12V and 24V DC, from 0.1



Plastic rack, Delrin

Complementary products



Locking castor, with central hole



Locking castor, with mounting plate