


Flat magnet




PLA

NdFeB


- **Shielded system**
- NdFeB magnets offer 10-20% more attraction force than SmCo magnets
- Max working temp : +80°C
- **Material, finish**
Galvanised steel body,
Magnetic core NeFeB




INCREASED STOCK



Type A



Type B



Type C

DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part number	Forme	ØD	ØD1	ØD2	ØD3	L	L1	Attraction force		Price each
								(N)	(g)	
PLA6-4/A	A	6 ^{+0,15}	-	-	-	-	4,5	5	1,0	3,24 €
PLA8-4/A	A	8 ^{+0,15}	-	-	-	-	4,5	13	1,5	3,36 €
PLA10-4/A	A	10 ^{+0,15}	-	-	-	-	4,5	25	2,5	3,92 €
PLA13-4/A	A	13 ^{+0,15}	-	-	-	-	4,5	60	4,5	4,05 €
PLA16-4/A	A	16 ^{+0,15}	-	-	-	-	4,5	95	6,5	4,85 €
PLA20-6/A	A	20 ^{+0,15}	-	-	-	-	6,0	140	15,0	7,30 €
PLA25-7/A	A	25 ^{+0,15}	-	-	-	-	7,0	200	22,0	10,95 €
PLA32-7/A	A	32 ^{+0,20}	-	-	-	-	7,0	350	40,0	17,17 €
PLA6-4/B	B	6 ^{+0,15}	6	M3	-	11,5	4,5	5	1,5	4,05 €
PLA8-4/B	B	8 ^{+0,15}	6	M3	-	11,5	4,5	13	2,0	4,20 €
PLA10-4/B	B	10 ^{+0,15}	6	M3	-	11,5	4,5	25	3,0	4,81 €
PLA13-4/B	B	13 ^{+0,15}	6	M3	-	11,5	4,5	60	5,0	5,02 €
PLA16-4/B	B	16 ^{+0,15}	6	M4	-	11,5	4,5	95	7,5	5,87 €
PLA20-6/B	B	20 ^{+0,15}	8	M4	-	13,0	6,0	140	16,0	9,98 €
PLA25-7/B	B	25 ^{+0,15}	8	M4	-	14,0	7,0	200	25,0	14,82 €
PLA32-7/B	B	32 ^{+0,20}	10	M5	-	15,5	7,0	350	48,0	20,02 €
PLA10-4/C	C	10 ^{+0,15}	-	-	M3	11,5	4,5	25	3,0	4,58 €
PLA13-4/C	C	13 ^{+0,15}	-	-	M5	12,5	4,5	60	5,0	5,02 €
PLA16-4/C	C	16 ^{+0,15}	-	-	M6	12,5	4,5	95	8,0	5,91 €
PLA20-6/C	C	20 ^{+0,15}	-	-	M6	16,0	6,0	140	16,0	10,01 €
PLA25-7/C	C	25 ^{+0,15}	-	-	M6	17,0	7,0	200	25,0	14,82 €
PLA32-7/C	C	32 ^{+0,20}	-	-	M6	17,0	7,0	350	48,0	20,38 €

Dimensions in mm

Our other products



ASL
45° Hoist ring for welding, for 45° lifts - for welding



DOG258
Motor-gearbox 12V and 24V DC, from 12 to 15 Nm



PM4
Worm and wheel set, Bronze



PSEC
Security pull handle, Thermoplastic



DILC
Indexing plunger with cam, with cam




PM3
Worm and wheel set, Hardened steel



P60
Worm and wheel gear reducer, up to 118 Nm



NPTR
Adjustable cross clamp, Adjustable



RPP5
RPP heavy duty timing belt, RPP5



VLBS
Folding lifting ring for welding, Folding - for



DKN
Bellows coupling Gerwah®, from 0.4 to



BFA
Shaft locking washer, E clip

Complementary products



PLA
Flat magnet, Flat magnet



PLA
Flat magnet, Flat magnet with threaded hole