


Magnetic stud with central hole



PLC

Ferrite

- Cup mounted Ferrite magnet with smooth bored hole
- Working temperature: -50°C to +100°C
- Good corrosion resistance
- Good mechanical resistance



Uses

- Mounting of objects where space is limited or mounting notice boards, protective covers etc
- Positioning of stops or inserts used in moulding machines

DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request


Part number	ØD	H	Ød	ØA	F (daN)	Weight (g)	Stock*	Price each 1 to 5
PLC50-10	50	10	8,5	22,0	18	85	✓	8,56 €
PLC63-14	63	14	6,5	24,0	29	197	✓	16,32 €
PLC80-18	80	18	6,5	11,5	54	458	✓	31,70 €

*Depending on availability - Dimensions in mm

PLT Magnetic stud with threaded hole

Ferrite

- Cup mounted Ferrite magnet with smooth bored hole
- Working temp.: -50°C to +100°C
- Good corrosion resistance
- Good mechanical resistance



Uses

- Fastening: protective casing, tool machines, support cables...
- Positioning: stops, inserts...
- Gripping: inaccessible places, transport


DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part number	ØD	L	H	Ød	ØM	F (daN)	Weight (g)	Stock*	Price each 1 to 5
PLT25-15	25	15	7	8	M4	4,0	22	✓	5,10 €
PLT32-15	32	15	7	8	M4	8,0	32	✓	6,18 €
PLT40-18	40	18	8	10	M5	12,5	60	✓	8,29 €
PLT50-22	50	22	10	12	M6	22,0	110	✓	10,05 €
PLT63-30	63	30	14	15	M8	35,0	240	✓	18,79 €
PLT80-34	80	34	18	20	M10	60,0	520	-	33,24 €
PLT100-42	100	42	22	22	M12	90,0	940	-	78,80 €

*Depending on availability - Dimensions in mm


Our other products



NCT
Square tube connector, Fixed angle



WS10
Drylin® W rail, Rail



EZY55
Stainless steel cylindrical stop, stainless steel



CLG1
Moulded plastic spur gear, Moulded plastic (nylon)



BLHT50
Right angled gearbox, from 11.50 to 30 Nm



BTC_M
End cap with threaded insert for square tube, With threaded insert



BTC
End cap for square tube, Standard



RTN
BoWex® curved tooth gear coupling, Nylon



FF20
Offset spur gear reducer, from 5.80 to 23 Nm



HTD5M_25
HTD Heavy duty timing pulley, HTD5 Steel



VLBG
Lifting ring, Rotating



RFV40
Stainless steel worm and wheel gearbox, up to 47 Nm

Complementary products



VAP
Magnetic stud with central hole, With central hole



PLC_PLT
Magnetic stud with central hole, With central hole