


Cylindrical holding magnets



PLM AINiCo, calibrated external diameter

- **Cylindrical gripping magnet**
- Shielded system
- Fixed used a press, shrink fitting or adhesive
- Dimension "H" can be reduced without affecting adhesive force
- Max working temp : 450°C
- **Material, finish**
Galvanised steel body,
Magnetic core AINiCo



DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request


Part number	ØD	L	H	Attraction force (N)	Weight (g)	Stock*	Price each. 1 to 5
PLM6-10/C	6	10	2	1,5	2	✓	5,30 €
PLM8-12/C	8	12	3	3,5	4	✓	5,76 €
PLM10-16/C	10	16	6	7,0	9	✓	6,16 €
PLM13-18/C	13	18	7	10,0	17	-	6,97 €
PLM16-20/C	16	20	5	18,0	29	-	8,84 €
PLM20-25/C	20	25	6	42,0	57	-	11,86 €
PLM25-30/C	25	30	5	96,0	110	-	20,87 €
PLM32-35/C	32	35	3	180,0	200	-	34,90 €
PLM40-45/C	40	45	5	240,0	420	-	78,33 €
PLM50-50/C	50	50	2	420,0	720	-	152,52 €

Flat gripping magnet

PLM

Hard ferrite core

- **Flat magnet without a threaded core**
- Shielded system
- These holding magnets can be force fitted or glued into positioning holes
- Max working temp : +200°C
- **Material, finish** :
Galvanised steel body,
Hard ferrite magnetic core




DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part number	ØD	L	Attraction force (N)	Weight (g)	Stock*	Price each. 1 to 5
PLM10-4/P	10 ^{±0,15}	4,5	4	2,0	✓	2,33 €
PLM13-4/P	13 ^{±0,15}	4,5	10	3,0	✓	2,62 €
PLM16-4/P	16 ^{±0,15}	4,5	18	4,5	-	3,10 €
PLM20-6/P	20 ^{±0,15}	6,0	30	10,0	✓	3,76 €
PLM25-7/P	25 ^{±0,15}	7,0	40	19,0	✓	4,12 €
PLM32-7/P	32 ^{±0,20}	7,0	80	30,0	✓	4,46 €
PLM40-8/P	40 ^{±0,20}	8,0	125	55,0	-	6,04 €
PLM50-10/P	50 ^{±0,20}	10,0	220	100,0	-	7,61 €
PLM63-14/P	63 ^{±0,20}	14,0	350	230,0	✓	13,36 €

Dimensions in mm

Our other products



NRR

Adjustable support clamp, Adjustable support clamp



SERB

Cam latch, Cam latch




SH2

Parallel axis helical gear, Machined plastic (delrin)



AT5M AT10M

AT type timing belt per metre, AT10 Steel cored polyurethane



PB

Plastic deep groove ball bearing, Plastic - glass balls material



UTKpwrr

V shaped channel UtiliTrak®, V rail



PLA

Flat magnet, Flat magnet



GALRUB

60mm rubber wheel for conveyor belt, Rubber



ZG1

Plastic spur gear, Machined plastic



CHA225

Screwed hinge with threaded insert, 225



GE_ET_2RS

Spherical bushing, Hard chromium /



NPCR

Adjustable cell support, Adjustable

Complementary products



PLM-20SC

Cylindrical magnet, Cylindrical magnet



PLM-20SC

Threaded cylindrical magnet, With threaded hole