


Cylindrical holding magnets



PLM AINiCo, calibrated external diameter

- Cylindrical gripping magnet
- Shielded system
- Fixed used a press, shrink fitting or adhesive
- Dimension "H" can be reduced without affecting adhesive force
- Max working temp : 450°C
- **Material, finish**
Galvanised steel body,
Magnetic core AINiCo



DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request


Part number	ØD	L	H	Attraction force (N)	Weight (g)	Stock*	Price each. 1 to 5
PLM6-10/C	6	10	2	1,5	2	✓	5,30 €
PLM8-12/C	8	12	3	3,5	4	✓	5,76 €
PLM10-16/C	10	16	6	7,0	9	✓	6,16 €
PLM13-18/C	13	18	7	10,0	17	-	6,97 €
PLM16-20/C	16	20	5	18,0	29	-	8,84 €
PLM20-25/C	20	25	6	42,0	57	-	11,86 €
PLM25-30/C	25	30	5	96,0	110	-	20,87 €
PLM32-35/C	32	35	3	180,0	200	-	34,90 €
PLM40-45/C	40	45	5	240,0	420	-	78,33 €
PLM50-50/C	50	50	2	420,0	720	-	152,52 €

Flat gripping magnet

PLM

Hard ferrite core

- Flat magnet without a threaded core
- Shielded system
- These holding magnets can be force fitted or glued into positioning holes
- Max working temp : +200°C
- **Material, finish**
Galvanised steel body,
Hard ferrite magnetic core



DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part number	ØD	L	Attraction force (N)	Weight (g)	Stock*	Price each. 1 to 5
PLM10-4/P	10 ^{±0,15}	4,5	4	2,0	✓	2,33 €
PLM13-4/P	13 ^{±0,15}	4,5	10	3,0	✓	2,62 €
PLM16-4/P	16 ^{±0,15}	4,5	18	4,5	-	3,10 €
PLM20-6/P	20 ^{±0,15}	6,0	30	10,0	✓	3,76 €
PLM25-7/P	25 ^{±0,15}	7,0	40	19,0	✓	4,12 €
PLM32-7/P	32 ^{±0,20}	7,0	80	30,0	✓	4,46 €
PLM40-8/P	40 ^{±0,20}	8,0	125	55,0	-	6,04 €
PLM50-10/P	50 ^{±0,20}	10,0	220	100,0	-	7,61 €
PLM63-14/P	63 ^{±0,20}	14,0	350	230,0	✓	13,36 €

Dimensions in mm

Our other products



PF40

Worm and wheel gear reducer, up to 18 Nm




WINGbrEcrou

Manually tightened wing nut DIN315, Brass DIN 315



PPC55

Pad eye on mounting plate squarred, Stainless steel



RPP8

RPP heavy duty timing belt, RPP8



CHAL3

Piano hinge, Steel




PCS37

Chain sprocket - steel, 9.525mm (DIN06B-1)



RDS

Safety washer Hygienic Usit®, Stainless steel



CF

Cam follower, Standard - steel



PNA_R

PERIFLEX elastic coupling,



PSG35

Spur gear - precision range, Stainless steel



CDR

Retaining cable for ball pin, Retaining



WJUM10

Drylin® W bearing block, Slide

Complementary products



PLM-SC

Magnetic stud with threaded hole, With threaded hole



PLM-SC

Magnetic stud with central countersunk hole, With milled bore