PERIFLEX® elastic coupling

PNA

Replacement tyre

- Tyre for PERIFLEX® coupling

- Replace the tyre without dismantling the
- Material natural rubber Tyre R (NR) equipped with disposed material in R
- Ouglity tyre X(1) with inserts mounted in X nattern

Assembly

- -The elastic coupling is delivered pre-assembled. To mount the coupling, remove the tyre and place the hubs and locking assemblies on their respective shafts. Bring the two assemblies together respecting the distance "O" and aligning the two hubs with a straight edge or template.
- Place the tyre between the two hubs ensuring there is minimum radial backlash (2-15mm depending on the size of the coupling). Then bring the two locking assemblies together, tightening pairs of diametrically opposite screws to the prescribed torque. As the rubber may decompress with time, re-check the torque after a few hours.







DISC	UUI	VIS	
Qty	1+	5+	10+
Dicc	Liet	_20/_	On roquo

Part number spare tyre	for PERIFLEX® coupling part number	Type of tyre	Stock*	Price each 1 to 4
203R	PNA2-203	R	-	92,88 €
206R	PNA6-206	R	V	113,52 €
210R	PNA16-210	R	V	171,31 €
214R	PNA40-214	R	V	266,28 €
218R	PNA63-218	R	V	276,60 €
414X	PNA40-214	X	-	268,36 €
418X	PNA63-218	X	-	295.18 €

^{*}Depending on availability - Dimensions in mm

Our other products



Half-rail guide, Wheel



Self-centering flanged locking assembly, Medium/high torque



Spur gear coaxial gearbox, from 15 to 40 Nm - Inline



H Type Guide units, For Ø40 actuators



Spherical tilt washer -DIN6319, concave



Adjustable latch clamp with strike plate, Stroke from 82mm to 92mm



Offset spur gear reducer, from 0.78 to 3.70 Nm



Small 6 lobe threaded handle - male, Duroplast - Stainless steel



24V DC motorisation kit, Planetary gears



Accessories, Fixing Ki



Spoked handwheel, Stainless steel 316



Telescopic drawer,

Complementary products



PERIFLEX® elastic coupling, Complete coupling