

PERIFLEX® elastic coupling

PNA

Replacement tyre

- Tyre for PERIFLEX® coupling

- Replace the tyre without dismantling the machine
- Material natural rubber Tyre R (NR) equipped with disposed material in R
- Quality tyre X(1) with inserts mounted in X pattern

Assembly

- The elastic coupling is delivered pre-assembled. To mount the coupling, remove the tyre and place the hubs and locking assemblies on their respective shafts. Bring the two assemblies together respecting the distance "O" and aligning the two hubs with a straight edge or template.
- Place the tyre between the two hubs ensuring there is minimum radial backlash (2-15mm depending on the size of the coupling). Then bring the two locking assemblies together, tightening pairs of diametrically opposite screws to the prescribed torque. As the rubber may decompress with time, re-check the torque after a few hours.



SAVE MONEY !
Only change the tyre

DISCOUNTS

Qty	1+	5+	10+
Disc.	List	-3%	On request

Part number spare tyre	for PERIFLEX® coupling part number	Type of tyre	Stock*	Price each 1 to 4
203R	PNA2-203	R	-	92,88 €
206R	PNA6-206	R	✓	113,52 €
210R	PNA16-210	R	✓	171,31 €
214R	PNA40-214	R	✓	266,28 €
218R	PNA63-218	R	✓	276,60 €
414X	PNA40-214	X	-	268,36 €
418X	PNA63-218	X	-	295,18 €

*Depending on availability - Dimensions in mm

Our other products



BMM

Knurled knob - male,
Knurled



Q6

Deep groove ball
bearing, Steel



RFK38C

Hypoid gearbox -
Stainless steel, up to
200 Nm



DCA

Suction cup, 1.5
bellows, nitrile



HTD5M_25

HTD Heavy duty
timing pulley, HTD5
Steel



ACA

Steel splined shaft,
Steel



RPCtc

Swivel castor with
central hole, Steel -
Polyamide - with
double brake



APBC

Circular rod, Round
rod



GPB

Threaded spherical
knob, Moulded thread



GE

Toggle latches,
Standard



NK27

Drylin®N miniature
guiding system, Width



Gdal

Double universal joint
eco series, Low duty

Complementary products



PNA

PERIFLEX® elastic
coupling, Complete
coupling