# PERIFLEX® elastic coupling

### **PNA**

### Replacement tyre

#### - Tyre for PERIFLEX® coupling

- Replace the tyre without dismantling the
- Material natural rubber Tyre R (NR) equipped with disposed material in R
- Ouglity tyre X(1) with inserts mounted in X nattern

#### Assembly

- -The elastic coupling is delivered pre-assembled. To mount the coupling, remove the tyre and place the hubs and locking assemblies on their respective shafts. Bring the two assemblies together respecting the distance "O" and aligning the two hubs with a straight edge or template.
- Place the tyre between the two hubs ensuring there is minimum radial backlash (2-15mm depending on the size of the coupling). Then bring the two locking assemblies together, tightening pairs of diametrically opposite screws to the prescribed torque. As the rubber may decompress with time, re-check the torque after a few hours.







DISC	UUI	VIS	
Qty	1+	5+	10+
Dicc	Liet	_20/_	On roquo

Part number spare tyre	for PERIFLEX® coupling part number	Type of tyre	Stock*	Price each 1 to 4
203R	PNA2-203	R	-	92,88 €
206R	PNA6-206	R	V	113,52 €
210R	PNA16-210	R	V	171,31 €
214R	PNA40-214	R	V	266,28 €
218R	PNA63-218	R	V	276,60 €
414X	PNA40-214	X	-	268,36 €
418X	PNA63-218	X	-	295.18 €

<sup>\*</sup>Depending on availability - Dimensions in mm

### Our other products



DEN

Bearing housing for miniature ballscrew, Bearing housing



Vertical toggle clamp, Vertical Lever Clamp stainless steel



Skive hobbed spur gears - precision range, Case hardened steel 20NCD2



Male clevis end, Steel short



\_\_\_\_

Right angle spiro bevel gearbox, Up to 43Nm



Hypoid gearbox -Stainless steel, up to 350 Nm



Wing nuts Hygienic Design®, Narrow



Telescopic drawer,



Moulded plastic bevel gear (nylon), 3:1



Cam follower, Standard - steel



Worm and wheel gear reducer, up to 980



Threaded stud -DIN976A, Steel

## Complementary products



PERIFLEX® elastic coupling, Complete coupling