

Universal threaded lifting hook

Base rotates through 360°

RUD PPS



- **Universal lifting hook for all applications.**
- Suitable for use with cables, round or synthetic slings and chains
- Double ball bearings allows for loads to turn or tilt
- Visual overload indication on hook
- Hook and latched manufactured from forged steel and 100% crack tested
- Hook has a pink thermochromic finish (High visibility)

Option

- Can be supplied with a longer thread and nut for use with a through hole or for mounting on lighter metals such as aluminium

Info

- Conforms to EU Directive 98/37/CE
- Load capacity doesn't change with load direction



4 Suitable for lifting in any direction
Factor of safety = 4

CE

DISCOUNTS

Qty	1+	5+	10+	15+
Disc.	List -3%	-6%	On request	

Part number	Load		A	B	C	D	SW	F	G	E	Weight (kg)	Torque de serrage (Nm)	Price each	
	CMU (t)	ØM												
PPS-M12	0,63	M12	13	75	18	40	36	18	41	116	0,4	10	✓	137,17 €
PPS-M16	1,5	M16	20	97	25	46	41	24	50	146	0,9	30	✓	172,68 €
PPS-M20	2,5	M20	28	126	30	61	55	30	61	187	1,7	70	-	216,51 €
PPS-M24	4,0	M24	36	150	35	78	70	36	77	227	3,5	150	-	304,36 €
PPS-M30	5,0	M30	37	174	40	95	85	45	93	267	7,5	225	-	444,13 €
PPS-M36	8,0	M36	49	208	48	100	90	54	102	310	9,2	410	-	702,55 €

*Depending on availability - Dimensions in mm

Our other products



M

Bellows cover,
Accessory:



BAN

Angular clamp,
Universal



HTD5M_09

HTD Heavy duty
timing pulley, HTD5
Steel



SMS

Spiral bevel gear, 1:1



PSG125HC

Skive hobbed spur
gears - precision
range, Case hardened
steel 20NCD2



NTM

Nylon tipped set
screw, Nylon-point



G1

Steel spur gear, Steel
20NCD2



BH01

Single housed
bearing, Bearing fitted
with adhesive



SLB

Indexing plunger,
steel class 5.8



Q4

Double row radial
contact ball bearing,



AT5M AT10M

AT type timing belt
per metre, AT5 Steel



LVT

Miniature motorised
actuator 1A, 1 amper

Complementary products



VRSSss

Male swivelling lifting
rings stainless steel,
Male swivelling - s...



WBGV

Lifting ring, Threaded



VRSF

Male swivelling lifting
ring, Male swivelling



VRM

Female swivelling
lifting rings, Female
swivelling