

# Universal threaded lifting hook

Base rotates through 360°

**RUD® PPS**



- **Universal lifting hook for all applications.**
- Suitable for use with cables, round or synthetic slings and chains
- Double ball bearings allows for loads to turn or tilt
- Visual overload indication on hook
- Hook and latched manufactured from forged steel and 100% crack tested
- Hook has a pink thermochromic finish (High visibility)

## Option

- Can be supplied with a longer thread and nut for use with a through hole or for mounting on lighter metals such as aluminium

## Info

- Conforms to EU Directive 98/37/CE
- Load capacity doesn't change with load direction



**4** Suitable for lifting in any direction  
Factor of safety = 4



**CE**


## DISCOUNTS

Qty	1+	5+	10+	15+
Disc.	List -3%	List -6%	On request	On request

Part number	Load CMU (t)	ØM	A	B	C	D	SW	F	G	E	Weight (kg)	Torque de serrage (Nm)	Price each
PPS-M12	0.63	M12	13	75	18	40	36	18	41	116	0.4	10	137,17 €
PPS-M16	1.5	M16	20	97	25	46	41	24	50	146	0.9	30	172,68 €
PPS-M20	2.5	M20	28	126	30	61	55	30	61	187	1.7	70	216,51 €
PPS-M24	4.0	M24	36	150	35	78	70	36	77	227	3.5	150	304,36 €
PPS-M30	5.0	M30	37	174	40	95	85	45	93	267	7.5	225	444,13 €
PPS-M36	8.0	M36	49	208	48	100	90	54	102	310	9.2	410	702,55 €

\*Depending on availability - Dimensions in mm

## Our other products



IN1  
Internal gear,  
Machined plastic  
(delrin)



PSG05  
Spur gear - precision  
range, Case hardened  
steel 20NCD2



STU  
Stroke rotary bushing,  
Steel



RT61ss  
Self-centering locking  
Assembly,  
Medium/low torque



TCLar  
Automatic chain  
tensioner, With wide  
guide




CMAss  
Eye bolt stainless  
steel, Stainless steel  
foot



PTA100ssEB  
Articulated foot with  
sheet metal base  
Ø100, 15000N



PRF\_PL\_4590  
Joining plate for  
aluminium profile,  
Joint plate - 45x90  
mm



ACL-PLAngle  
Joining plate for  
aluminium profile,  
Angle connection



PAMF100EB  
Articulated foot with  
sheet metal base  
Ø100, Articulated foot



HCA  
Magnetic screw with  
socket, Steel



EHD08-9  
Internal epicyclic  
servo reducers, from  
35 to 50 Nm

## Complementary products



VRSSss  
Male swivelling lifting  
rings stainless steel,  
Male swivelling - s...



WBGV  
Lifting ring, Threaded



VRSF  
Male swivelling lifting  
ring, Male swivelling



VRM  
Female swivelling  
lifting rings, Female  
swivelling