

# Solid stainless steel articulated foot Ø30 Sta


## PRS30

## Max load up to 10,000N

- **Levelling foot**
- Oscillation +/- 15° with respect to the axis
- With non-slip sole
- **Materials:**
  - Base: AISI 304 stainless steel
  - Rod: stainless steel AISI 304 (nut not supplied)
  - Sole: rubber NBR hardness 70° Shore, non-slip

### Advantages

- The rod with its ball-and-socket arrangement allows self-alignment with the ground
- The sole is designed to give flexibility and grip



### DISCOUNTS

Qty	1+	6+	10+	15+
Disc.	Net	-5%	-10%	On request

Part N°	ØM	A	B	ØD	A/F	G	H	H1	Static load (N)	Price each 1 to 5
PRS30-6-25	M6	23,5	25	30	12	13	48,5	49	5000	22,04 €
PRS30-6-50	M6	23,5	50	30	12	13	73,5	74	5000	23,47 €
PRS30-6-75	M6	23,5	75	30	12	13	88,5	89	5000	24,94 €
PRS30-8-25	M8	23,5	25	30	12	13	48,5	49	8000	22,04 €
PRS30-8-50	M8	23,5	50	30	12	13	73,5	74	8000	23,47 €
PRS30-8-75	M8	23,5	75	30	12	13	88,5	89	8000	24,94 €
PRS30-8-100	M8	23,5	100	30	12	13	123,5	124	8000	28,62 €
PRS30-10-25	M10	23,5	25	30	12	13	48,5	49	10000	22,04 €
PRS30-10-50	M10	23,5	50	30	12	13	73,5	74	10000	23,47 €
PRS30-10-75	M10	23,5	75	30	12	13	88,5	89	10000	24,94 €
PRS30-10-100	M10	23,5	100	30	12	13	123,5	124	10000	28,62 €
PRS30-10-125	M10	23,5	125	30	12	13	148,5	149	10000	26,92 €
PRS30-12-25	M12	23,5	25	30	12	13	48,5	49	10000	22,04 €
PRS30-12-50	M12	23,5	50	30	12	13	73,5	74	10000	23,47 €
PRS30-12-75	M12	23,5	75	30	12	13	88,5	89	10000	24,94 €
PRS30-12-100	M12	23,5	100	30	12	13	123,5	124	10000	26,41 €
PRS30-12-125	M12	23,5	125	30	12	13	148,5	149	10000	27,89 €
PRS30-12-150	M12	23,5	150	30	12	13	173,5	174	10000	29,36 €

\* Subject to available stocks- All dimensions in mm

## Our other products



BLHT30  
Right angled gearbox,  
from 1.65 to 4.40 Nm



SHTP  
Drylin® Linear table,  
Economy range



PAT85  
Pressed stainless  
steel articulating foot  
Ø85, Ø 85



M0  
Worm and wheel set,  
Machined plastic  
(delrin)



PTAF80-PAMF80  
Articulated fixable  
foot with pressed  
base Ø80, Ø 80



SRG  
Adjustable latch  
clamp with strike  
plate, Stroke from  
117,4mm to 128mm



DKONSL  
Silicone conical elasto  
buffer, Male mounting



MCL  
Cylindrical threaded  
sleeve, Cylindrical -  
steel



SHSS  
Shoulder screw  
stainless steel 416,  
Pre-treated 416



CABPVC  
PVC covered  
galvanized steel  
cable, Galvanised



BH01  
Single housed  
bearing, Bearing fitted  
with adhesive



AWMP  
Aluminium shaft for  
linear guide,  
Aluminium

## Complementary products



PR550  
Stainless steel  
articulated foot Ø50,  
Ø 50



PAM\_SS  
Stainless steel  
articulated levelling  
foot, Ø 30 & 40