



Stainless steel swivelling foot, bolt-down

Max load 25,000N



PTKFss

- "Teknohygienic" swivelling foot
- Materials:
 - Base: stainless steel 304
 - Stem: stainless steel 304
 - Blind nut: stainless steel 304
- Sole: NBR rubber Shore hardness 90°

For the food industry

Avoids water retention


stainless steel

Advantages

- The 3-A standard designates products that are designed for the dairy, food and pharmaceutical industries where strict hygiene rules apply.
- Smooth finished foot with a wiper seal between the stem and the nut and around the swivel to prevent accumulation of dirt or retention of water
- Suitable for cleaning with water or chemicals
- USDA approved

Info.

- Do not forget to order the PTKF-M12/SS 3-A approved blind nut



Blind M12 nut

DISCOUNTS

| Qty | 1+ | 6+ | 10+ |
|-------|------|-----|------------|
| Disc. | List | -5% | On request |

| Part number | Adjustable range | ØM | E | A | B | ØD | SW | ØD1 | D2 | CH | H2 | H3 | H1 | I | Static load (N) | Price each 1 to 5 |
|-------------------|------------------|----|----|-----|-----|----|----|-----|----|-----|-----|-----|----|-------|-----------------|-------------------|
| PTKF80-16-140/SS | M16 | 45 | 53 | 140 | 80 | 13 | 24 | 60 | 20 | 114 | 159 | 193 | 54 | 20000 | 102,12 € | |
| PTKF80-16-190/SS | M16 | 70 | 53 | 190 | 80 | 13 | 24 | 85 | 20 | 139 | 209 | 243 | 54 | 20000 | 105,01 € | |
| PTKF80-20-140/SS | M20 | 45 | 53 | 140 | 80 | 17 | 30 | 60 | 26 | 114 | 159 | 193 | 54 | 20000 | 92,37 € | |
| PTKF80-20-142/SS | M20 | 55 | 53 | 142 | 80 | 17 | 30 | 70 | 26 | 123 | 178 | 195 | 54 | 20000 | 95,30 € | |
| PTKF80-20-190/SS | M20 | 70 | 53 | 190 | 80 | 17 | 30 | 85 | 26 | 139 | 209 | 243 | 54 | 20000 | 105,91 € | |
| PTKF80-24-140/SS | M24 | 45 | 53 | 140 | 80 | 20 | 35 | 60 | 30 | 114 | 159 | 193 | 54 | 20000 | 95,92 € | |
| PTKF80-24-190/SS | M24 | 70 | 53 | 190 | 80 | 20 | 35 | 85 | 30 | 139 | 209 | 243 | 54 | 20000 | 112,90 € | |
| PTKF100-16-140/SS | M16 | 45 | 56 | 140 | 100 | 13 | 24 | 60 | 20 | 117 | 162 | 196 | 69 | 25000 | 93,26 € | |
| PTKF100-16-190/SS | M16 | 70 | 56 | 190 | 100 | 13 | 24 | 85 | 20 | 142 | 212 | 246 | 69 | 25000 | 110,14 € | |
| PTKF100-20-140/SS | M20 | 45 | 56 | 140 | 100 | 17 | 30 | 60 | 26 | 117 | 162 | 196 | 69 | 25000 | 97,49 € | |
| PTKF100-20-190/SS | M20 | 70 | 56 | 190 | 100 | 17 | 30 | 85 | 26 | 142 | 212 | 246 | 69 | 25000 | 111,05 € | |
| PTKF100-24-140/SS | M24 | 45 | 56 | 140 | 100 | 20 | 35 | 60 | 30 | 117 | 162 | 196 | 69 | 25000 | 105,20 € | |
| PTKF100-24-190/SS | M24 | 70 | 56 | 190 | 100 | 20 | 35 | 85 | 30 | 142 | 212 | 246 | 69 | 25000 | 118,02 € | |
| PTKF100-30-135/SS | M30 | 40 | 56 | 135 | 100 | 26 | 42 | 60 | 36 | 117 | 157 | 191 | 69 | 25000 | 115,08 € | |
| PTKF100-30-185/SS | M30 | 65 | 56 | 185 | 100 | 26 | 42 | 85 | 36 | 142 | 207 | 241 | 69 | 25000 | 125,34 € | |

Blind M12 nut

| | | | | | | | | | | | | | | | | |
|-------------|-----|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---------|
| PTKF-M12/SS | M12 | | | | | | | | | | | | | | | 13,82 € |
|-------------|-----|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---------|

Dimensions in mm

Our other products



P45
Worm and wheel gear reducer, up to 40 Nm



GE_ES_2RS
Spherical bushing, Steel / steel with seals



BAC105
Storage bin, 8mm



RTE
Rotex®, jaw coupling, steel



TBE16
Economic mini-table with trapezoidal leadscrew, 5kg



PP60
Worm and wheel gear reducer, from 17.80 to 34 Nm



CHB
Feet, For CHB gearbox



VML
Stainless steel hexagonal headed thumb screw, Male



JCDss
Double universal joint - Stainless steel, Low



PR40
Articulated foot Ø50, Ø 50



HW_HT
Half-rail guide, Wheel



YG4
HEAVY DUTY spur gear, Steel 35NCD6

Complementary products



PTKFss
Fixable foot for the food industry, Stainless steel - 3-A standard