## Floway2® roller track and basic support

#### RAG-FLOW2

### **Principal of operation**



- The Floway-2® roller track allows storage systems to be created for plastic boxes or cardboard cartons

#### Support

- For easy installation of roller tracks
- Suitable for use in gravity feed conveyors
- Material:


Electro-galvanised steel

#### Assembly

- Slide the roller track into the end support
- Position the complete assembly on the supporting structure
- Track can be locked in place using a screw (tapped hole to be drilled on site)



Basic support





Support with stop





# 条弧 Floway2® roller track and basic support

### For transporting and storage

#### RAG-FLOW2



- Chromed steel auide
- (no deformation under load) - Rollers rotate on steel axles
- Colour: Black

#### Special Features - The possibility of being able to stagger



the position of the rails increases the performance Ø25 22.4. of the system 34 25 Roller 30.4 track (2x) Ø6.8 10 10 Basic RAG-FLOW2-B RAG-FI OW2-A

# DISCOUNTS Roller track DISCOUNTS Basic support Olé 1+ 5+ 10+ Olé 1+ 50+ 100+

	Roller track		D	isc. Prix	-5%	On request	Disc.	Prix	-5%	On	request
Part number p1				Length N° of P2 L with roller rollers			Max load Stock*Price each				
	Fait ilullibei	PI	P2	_	with 10	ilei Tolleis	perior	iei (ki	9)		144
	RAG-FLOW2-1000	35	41	1000 ±1	980	34	1	0			24,51 €
	DAC ELOMO 0000	0.5	20	0046 . 1	0010	70	- 4	_		-	40.00.0

Basic	su	pį	oor

Part number	Description	Thickness	Weight (g)	Stock*	Price each 1 à 49
RAG-FLOW2-A	Basic support	2	124	V	8,16 €
RAG-FLOW2-B	Support with stop	2	141	-	8,16 €

<sup>\*</sup>Subject to available stocks - Dimensions in mm





#### Our other products



Double universal joint - Stainless steel, Low duty



Long-Lok slotted spring plunger with ball tip, LONG-LOK -Stainless ...



Anti-vibration machine mount, Oval base plate



Spur gear coaxial gearbox, from 0.90 to 2.80 Nm - Inline



Flanged polymer bush, Universal polymer



Worm - precision range, Stainless steel



Folding lifting ring for welding, Folding - for welding



Crossed helical gear crossed axis at 90°, Steel 20NCD2



Heavy duty plastic hinge, opens 180°, Heavy duty - Opens



Lifting ring, Threaded



Panamech, Multi-Beam, Aluminium with clamping jaw



Spur gear coaxial gearbox, from 20 to 68 Nm - Inline

### Complementary products



Floway2® roller track, Roller track



Cylindrical brush track, For gentle conveying and handling