Floway2® roller track and basic support

RAG-FLOW2

Principal of operation



- The Floway-2® roller track allows storage systems to be created for plastic boxes or cardboard cartons

Support

- For easy installation of roller tracks
- Suitable for use in gravity feed conveyors
- Material:


Electro-galvanised steel

Assembly

- Slide the roller track into the end support
- Position the complete assembly on the supporting structure
- Track can be locked in place using a screw (tapped hole to be drilled on site)



Basic support





Support with stop





条弧 Floway2® roller track and basic support

For transporting and storage

RAG-FLOW2



- Chromed steel auide
- (no deformation under load) - Rollers rotate on steel axles
- Colour: Black

Special Features - The possibility of being able to stagger

- oller track Basic SUPDON

the position of the rails increases the performance Ø25 22.4. of the system 34 25 Roller 30.4 track (2x) Ø6.8 10 10 Basic RAG-FLOW2-B RAG-FI OW2-A

DISCOUNTS Roller track DISCOUNTS Basic support

		_		01	101	Q.C		001		1001
Roller track		Di	sc. Prix	-5%	On request	Disc.	Prix	-5%	On	request
				ngth	N° of		load	Sto	ck*	Price each
Part number	P1	P2	L	with rol	ler rollers	per roll	ler (ko	1)	·	1 à 4
RAG-FLOW2-1000	35	41	1000 ±1	980	34	1	0		/	24,51 €

Part number	ı	Descri	iption	Thi	ckness	Weight (q)	Stock*	Price each 1 à 49
Basic support								
RAG-FLOW2-2000	35	33 2	2046 ±1	2016	70	10	V	40,33 €
TIMAT LOWE 1000	00		1000 ±1	300		10		27,01 C

Support with stop *Subject to available stocks - Dimensions in mm

Basic support



124

141



8,16€

8.16 €

RAG-FLOW2-A

RAG-FLOW2-B

2

2

Our other products



SFR69K-CLF

Quarter turn latch for the food industry. Stainless steel key



Double row radial contact ball bearing,



Adjustable clamp, Adjustable

NSR



Sliding lock adjustment system. Sliding lock for square profile



Angular connector, Universal angular connector



Lip seal for panel, Door seal - Ø 6mm



Crossed helical gear crossed axis at 90°. Machined plastic (delrin)



High helix leadscrew. Leadscrew only - up to 40mm per rotation



Telescopic drawer,



Eco range Spur gear, Steel C45



Hexagonal nut -DIN934, Box set of steel nuts



Worm and wheel gear reducer, up to 164 Nm

Complementary products



Floway2® roller track, Roller track



Cylindrical brush track, For gentle conveying and handling