Floway2® roller track and basic support

RAG-FLOW2

Principal of operation



- The Floway-2® roller track allows storage systems to be created for plastic boxes or cardboard cartons

Support

- For easy installation of roller tracks
- Suitable for use in gravity feed conveyors
- Material:


Electro-galvanised steel

Assembly

- Slide the roller track into the end support
- Position the complete assembly on the supporting structure
- Track can be locked in place using a screw (tapped hole to be drilled on site)



Basic support





Support with stop





条弧 Floway2® roller track and basic support

For transporting and storage

RAG-FLOW2



- Chromed steel auide
- (no deformation under load) - Rollers rotate on steel axles
- Colour: Black

Special Features - The possibility of being able to stagger



the position of the rails increases the performance Ø25 22.4. of the system 34 25 Roller 30.4 track (2x) Ø6.8 10 10 Basic RAG-FLOW2-B RAG-FI OW2-A

DISCOUNTS Roller track DISCOUNTS Basic support Olé 1+ 5+ 10+ Olé 1+ 50+ 100+

	Roller track		D	isc. Prix	-5%	On request	Disc.	Prix	-5%	On	request
Part number p1				Length N° of P2 L with roller rollers			Max load Stock*Price each				
	Fait ilullibei	PI	P2	_	with 10	ilei Tolleis	perior	iei (ki	9)		144
	RAG-FLOW2-1000	35	41	1000 ±1	980	34	1	0			24,51 €
	DAC ELOMO 0000	0.5	20	0046 . 1	0010	70	- 4	_		-	40.00.0

Basic	su	pį	oor

Part number	Description	Thickness	Weight (g)	Stock*	Price each 1 à 49
RAG-FLOW2-A	Basic support	2	124	V	8,16 €
RAG-FLOW2-B	Support with stop	2	141	-	8,16 €

^{*}Subject to available stocks - Dimensions in mm





Our other products



Connecting kits, XY linking kit



Manual workbench press, Force up to 200ka



Threaded eye hook stainless steel, Stainless steel



Spring loaded toggle latch, Standard (GP75)



Parallel axis helical gear, Steel 20NCD2



Idler chain sprocket, For standard applications



Slip friction clutch, 4 to 2600 Nm



180° ball and socket joints, Steel



Aluminium profile feet support, For feet or casters



Mini plain bearing ball transfer unit, For countersinking



Flexible tube handle, PVC



Masterplate® glueable insert Ø19/Ø20, Cylindrical with nut

Complementary products



Floway2® roller track, Roller track