

Locking castor with central hole





RIM

For loads up to 1000kg

- A combination of a swivel castor and an adjustable locking support
- Used to easily support and moving machines or other heavy equipment and then positioning them in a very stable manner.
- Installation starts by lowering the locking support using a nut.
- With the wheel no longer resting on the ground, the supported unit can be levelled despite any irregularities in the floor.
- Operating temperature range: -30 to +80°C

Materials

- Polyamide central control cross nut
- Anti-skid rubber mount allowing absorption of vibration and noise
- Body: Moulded cast aluminium body, hammered ivory paint finish
- Swivel system provided by 2 ball rings
- Mounting plate has a threaded central hole, threaded rod and nut supplied.
- Wheel: Black polyamide Shore D 70



DISCOUNTS

Qty	1+	5+	14+
Disc.	List	-5%	On request

Part number	ØA	B	H1	H2	ØT	Swivel interference ØK	Load (kg)	Price each 1 to 5
RIM42-60/TCE	42	20	71	81	M8	84	60	46,66 €
RIM50-280/TCE	50	25	82	92	M12	101	280	74,11 €
RIM63-550/TCE	63	28	103	118	M12	125	550	100,71 €
RIM75-800/TCE	75	30	120	132	M16	142	800	111,33 €
RIM75-1000/TCE	75	30	120	132	M16	142	1000	132,76 €

Dimensions in mm

HPC

WEB
2020

www.hpceurope.com

Tél: 0 825 88 5000 Service 0,15 €/min + prix appel

Our other products



UCF_PBT
Stainless steel/Polymer flanged bearing, Polymer and stainless steel



SRG
Adjustable latch clamp with strike plate, Stroke from 117,4mm to 128mm



PW_PWG25
Worm - precision range, Stainless steel



M0
Worm and wheel set, Machined plastic (delrin)



PCS6255
Chain sprocket - Stainless steel, 15.875mm (DIN 08B-1)



ACA
Steel splined shaft, Steel



PDD
Actuating plunger, Non-rotating detector shaft



CHAR6035
Spring hinge, screwed/welded



GLT3E-50
Telescopic drawer,



M2
Worm and wheel set, Hardened steel



PRF_ECL
Nut for aluminium profile, Stainless steel square nut with tab



BOX-TOR-TOOL
Box set of tool for Nitrile O-rings, Extraction tools

Complementary products



RIMple
Locking castor, with mounting plate



PDR-RD
Mounting feet with integrated castors, Offset castor