


- **Easily installed**
- Uses the space between two drive sprockets
- Self positioning
- Dampens vibration
- Self lubricating
- Working temperature: -20°C to +70°C  
(except RLR20-030: -4°C to +40°C)
- Normal resistance to UV radiation
- Material: polymer

### Use

- Multiple tensioners can be used in series on long chains or in parallel on multiple chains
- On triple chains, tensioners are only needed on inner and outer strands

### Advantages

- Works equally as well on vertically or diagonally mounted chains
- Does not require fixing or special installation



**Very easy  
to use**

### DISCOUNTS

Qty	1+	6+	21+
Disc.	List	-5%	On request

Part number	No. of teeth	Ref. ISO	Pitch (mm)	do	Internal diameter di	Max. diameter deviation S	A	Static force of max. expansion (N)	Max. chain speed (m/s)	Stock*	Price each 1 to 5
RLR05-030	30	05B	8,00	76,5	65,0	20	104,0	2,9	5,0	-	105,32 €
RLR06-030	30	06B	9,52	91,1	73,0	25	122,0	15,2	5,2	✓	91,26 €
RLR06-036	36	06B	9,52	109,0	89,0	25	143,0	28,5	5,2	✓	103,31 €
RLR08-026	26	08B	12,70	105,5	87,5	27	135,8	13,4	7,5	✓	84,91 €
RLR08-030	30	08B	12,70	121,5	101,6	30	161,6	14,2	8,6	✓	98,03 €
RLR08-034	34	08B	12,70	137,5	115,4	30	165,0	22,0	8,8	✓	111,09 €
RLR10-026	26	10B	15,88	128,4	105,0	28	153,0	28,2	4,2	✓	103,54 €
RLR10-030	30	10B	15,88	148,0	124,6	33	177,0	23,0	8,8	-	119,11 €
RLR10-034	34	10B	15,88	170,0	141,0	38	217,0	45,1	8,8	-	135,22 €
RLR12-026	26	12B	19,05	155,0	127,6	35	209,5	39,2	5,4	✓	125,17 €
RLR12-030	30	12B	19,05	182,2	153,1	45	242,0	32,2	6,2	-	144,53 €

\*Depending on availability - Dimensions in mm


## Installation

Roll-Ring® chain tensioners do not require any maintenance and can be installed on practically all chain drive systems. **Their installation takes virtually no time and is inexpensive.** The only conditions that must be met to be able to use them are:

- The gap between the chain strands must be sufficiently large.
- The distance between the chain sprockets must be sufficiently large.


We recommend that you position the tensioner between two chain strands so that there is at least the equivalent of one chain pitch between the Roll-Ring® and the smallest sprocket. The Roll-Ring® can also be mounted in an alternative but efficient manner to that previously described, simply verify that the pre-load is sufficiently high. We do however; recommend that you carry out tests if this is done.

Roll-Ring® chain tensioners can be used in series on the same chain strand. They can also be used in parallel on each strand of a multiple strand chain. For example, a triple strand chain requires two Roll-Ring® tensioners on the outside strands.




## Advantages


### Typical Roll-Ring® applications



Vibrations on a non tensioned chain



The Roll-Ring® tensions and dampens the chain



## Our other products



BZY  
Cylindrical elasto  
mount, Steel



PSG25S  
Spur gear - precision  
range, Stainless steel  
316



PCS62K  
Chain sprocket with  
hardened teeth,  
15.875mm (DIN10B-1)



ALIDRP240  
24V DC power supply,  
10 A



PTA50ssEB  
Articulated foot with  
sheet metal base  
Ø50, Articulated foot



NT92  
Spur gear coaxial  
gearbox, from 15 to  
40 Nm - Inline



BCAss  
Stainless steel splined  
bush, Inox



AK  
Bellows coupling  
Gerwah®, from 36 to  
800Nm



KKP-AR  
Linear bearing with  
inclined ball tracks,  
3000 N



HTD14M\_55  
HTD Heavy duty  
timing pulley, HTD14



TS01\_TW01  
Drylin® T linear slide,  
up to 7000 N




DH  
Dowel pin, Solid DIN  
6325

## Complementary products



SUA4  
Single chain supplied  
by the metre, Steel



SBS\_M  
Single chain supplied  
by the metre,  
Stainless steel



TCXR  
Automatic chain  
tensioner, With  
stainless steel  
sprocket



TCLar  
Automatic chain  
tensioner, With wide  
guide