


SZZ

With protective shields

- Radial contact ball bearings
- Single row of balls
- With 2 protective shields (ZZ joints)
- Tolerance: P6/ABEC3
- Material: stainless steel AISI 440C
- Static and dynamic loads : these bearings can handle approx 70% of the same loads that an equivalent steel bearing will accept
- Max. working temperature: +80°C



stainless steel



DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-10%	-15%	-20%	On request

Part number	ØA	ØD	E	Dynamic load (N)	Static load (N)	Stock*	Price each 1 to 5
S682ZZ	2	5	2,3	137,29	39,23	✓	23,04 €
S683ZZ	3	7	3,0	254,97	78,45	✓	17,23 €
S684ZZ	4	9	4,0	509,95	176,52	✓	17,23 €
S685ZZ	5	11	5,0	598,21	225,55	✓	16,30 €
S686ZZ	6	13	5,0	853,18	343,23	✓	16,30 €
S687ZZ	7	14	5,0	961,05	402,07	✓	17,30 €
S688ZZ	8	16	5,0	1029,70	460,91	✓	19,88 €
S608ZZ	8	22	7,0	2726,25	1068,92	✓	35,35 €
S689ZZ	9	17	6,0	1098,34	529,56	-	21,17 €
S6800ZZ	10	19	5,0	1441,58	657,05	✓	38,63 €
S6801ZZ	12	21	5,0	1569,06	853,18	✓	52,95 €
S6802ZZ	15	24	5,0	2029,98	1225,83	✓	67,11 €
S6803ZZ	17	26	5,0	1824,04	1196,41	-	73,48 €
S6804ZZ	20	32	7,0	3314,65	2029,98	✓	87,13 €

*Depending on availability - Dimensions in mm

Our other products



GCL

Linear ball slide -
Stainless steel balls,
Chariot - from 516 N
to 8...



FCHN_CHNSS

Straight long link
chain, Galvanised
steel




SBF

Open flange bearing
unit for food industry,
cover



T39_T49

Extension spring in
metre length stainless
steel, by the metre



GLT2-27

Telescopic drawer
runners for groove
mounting, Partial
extension



M2

Worm and wheel set,
Hardened steel



M1

Worm and wheel set,
Non hardened steel



BPPL

Assembly tool for
carrier ball, Mounting
tool



H0

Crossed helical gear
crossed axis at 90°,
Steel 20NCD2



EFTC

Fixing support,
Stainless steel



UFX

Uneflex® elastic
coupling, range



CHA225

Screwed hinge with
threaded insert, 225
degrees

Complementary products



SF_ZZ

Deep groove ball
bearing, Stainless
steel



S_2RS

Deep groove ball
bearing, Stainless
steel



FUSS

Bearing locknut, Self
locking locknut -
stainless steel lock
washer