

- Female threaded rod end
- Axial static load = 0.2 x radial static load
- Materials:

Housing: stainless steel 303

Insert: stainless steel 303

Sphere: stainless steel 420


Coating: UNIFLON® between ring and sphere

Advantages

- Long life expectancy
- Low friction
- No maintenance required
- Corrosion resistant

Uses

- Oscillating movement in hostile environments (water, salt, dampness, other difficult atmospheric conditions...)



Swiss precision



stainless steel

DISCOUNTS

| | | | |
|-------|------|------|------------|
| Qty | 1+ | 10+ | 24+ |
| Disc. | List | -20% | On request |

| Part number | ØA | B | ØD | F | G | H | ØJ | K | L | M | O | W | X |
|-------------|----|----|----|----|----|-------|-------|-------|-------|------------|-------|----|-------|
| SFE3.45 | 3 | 10 | 12 | 21 | 27 | 4,50 | 5,00 | 6,50 | 3,00 | M3 x 0,50 | 5,18 | 6 | 5,50 |
| SFE5.45 | 5 | 14 | 16 | 27 | 35 | 6,00 | 7,50 | 9,50 | 4,00 | M5 x 0,80 | 7,71 | 8 | 8,00 |
| SFE6.45 | 6 | 14 | 18 | 30 | 39 | 6,75 | 9,50 | 12,00 | 5,00 | M6 x 1 | 8,98 | 9 | 10,00 |
| SFE8.45 | 8 | 17 | 22 | 36 | 47 | 9,00 | 12,50 | 16,00 | 5,00 | M8 x 1,25 | 10,40 | 12 | 13,00 |
| SFE10.45 | 10 | 20 | 26 | 43 | 56 | 10,50 | 15,00 | 19,00 | 6,50 | M10 x 1,50 | 12,92 | 14 | 16,00 |
| SFE12.45 | 12 | 22 | 30 | 50 | 65 | 12,00 | 17,50 | 22,00 | 6,50 | M12 x 1,75 | 15,43 | 16 | 18,00 |
| SFE14.45 | 14 | 27 | 34 | 57 | 74 | 13,50 | 20,00 | 25,00 | 8,00 | M14 x 2 | 16,86 | 19 | 21,00 |
| SFE16.45 | 16 | 33 | 38 | 64 | 83 | 15,00 | 22,00 | 27,00 | 8,00 | M16 x 2 | 19,39 | 21 | 24,00 |
| SFE18.45 | 18 | 36 | 42 | 71 | 92 | 16,50 | 25,00 | 31,00 | 10,00 | M18 x 1,50 | 21,89 | 23 | 27,00 |

| Part number | Radial static load (daN) | Sphere ØE | Weight (g) | Price each 1 to 5 |
|-------------|--------------------------|-----------|------------|-------------------|
| SFE3.45 | 160 | 6,00 | 7 | 198,57 € |
| SFE5.45 | 250 | 11,11 | 14 | 129,44 € |
| SFE6.45 | 300 | 12,70 | 22 | 115,16 € |
| SFE8.45 | 450 | 15,88 | 38 | 122,53 € |
| SFE10.45 | 600 | 19,05 | 70 | 149,10 € |
| SFE12.45 | 770 | 22,23 | 110 | 172,26 € |
| SFE14.45 | 940 | 25,40 | 150 | 167,32 € |
| SFE16.45 | 1140 | 28,58 | 200 | 303,54 € |
| SFE18.45 | 1370 | 31,75 | 280 | 540,80 € |

Dimensions in mm

Our other products



WINGbr

Wing screw, hand tightened DIN316, Brass DIN 316



CHTRP

Single and dual output gearboxes, Up to 87,3Nm



GLT3E-58

Telescopic drawer,



DPAR_DKON

Conical elasto buffer, Steel



ERF

Quick fitting threaded cable terminal, Cable terminal with threaded ...



EML

Stainless steel hexagonal headed thumb nut, Lobed handscrew



AT5P_AT10P

Connecting plate for AT type timing belts, AT10




BLHM30

Right angled gearbox, double output shafts, up to 4.4 Nm



PARF110

Pressed steel base rigid foot, Swivelling



T5M_T10M

T type timing belt per metre, T5 Steel cored



H02SS

Needle roller universal joint - Stainless steel,



T10-BAR

T type tooth bar stock, T10

Complementary products



CFF_SS

Female rod ends DIN ISO12240-4, Stainless steel / bronze - Economy r...



CFF

Female rod ends DIN ISO12240-4, Steel / bronze