



# Magnetic stud with central hole

AlNiCo

VAP



- AlNiCo magnets with central through drilled mounting hole
- Both faces are machine finished and have a strong attraction force in a reduced size
- Working temperature -50°C to +450°C
- Good shock resistance

**For recessed mounting, following precautions should be observed**

- in a non-ferrous support: none specified
- in a ferrous support: magnet should be isolated from the support by an air gap or non-ferrous material

## Applications

- Suitable for fixing or positioning of components in reduced spaces and possibly subject to high temperatures
- Positioning of inserts in moulding machines...




## DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part number	ØD	Ød	E	F (daN)	Weight (g)	Stock*	Price each 1 to 5
VAP19-8	19	3,5	8,0	3,0	18	✓	6,65 €
VAP28-9	29	5,0	9,0	5,0	46	✓	10,62 €
VAP38-11	38	5,0	10,5	9,5	97	-	15,71 €

\*Depending on availability - Dimensions in mm

## Our other products



AC

Strike for toggle latch,  
12,13,18 and 20mm



PITA

Locking bolt, with T  
handle



CHAE4060PA

Decorative  
asymmetric screwed  
hinge, Polyamide



SH2

Parallel axis helical  
gear, Machined plastic  
(delrin)



BLM

Spring loaded plunger  
with ball tip, Stainless  
steel body



NT63

Spur gear coaxial  
gearbox, from 8 to 20  
Nm - Inline



GLT2-17

Telescopic drawer  
runners for groove  
mounting, Partial  
extension



G1

Steel spur gear, Steel  
20NCD2



GMC

Flat profile - Round  
guide, Flat profile -  
round guide



NJM

Multiple junction  
clamp, Multiple



M

Bellows cover,  
Accessory:



HRV

V-rail guidance  
Simple Select®  
system, Rail with  
carriage

## Complementary products



PLC\_PLT

Magnetic stud with  
central hole, With  
central hole



PLC\_PLT

Magnetic stud with  
threaded hole, With  
threaded hole