



Magnetic stud with central hole

AlNiCo

VAP



- AlNiCo magnets with central through drilled mounting hole
- Both faces are machine finished and have a strong attraction force in a reduced size
- Working temperature -50°C to +450°C
- Good shock resistance

For recessed mounting, following precautions should be observed

- in a non-ferrous support: none specified
- in a ferrous support: magnet should be isolated from the support by an air gap or non-ferrous material

Applications

- Suitable for fixing or positioning of components in reduced spaces and possibly subject to high temperatures
- Positioning of inserts in moulding machines...



DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part number	ØD	Ød	E	F (daN)	Weight (g)	Stock*	Price each 1 to 5
VAP19-8	19	3,5	8,0	3,0	18	✓	6,65 €
VAP28-9	29	5,0	9,0	5,0	46	✓	10,62 €
VAP38-11	38	5,0	10,5	9,5	97	-	15,71 €

*Depending on availability - Dimensions in mm

Our other products



Threaded cylindrical magnet, With threaded hole



Handwheel with handle, Thermosetting plastic - stainless steel hub



Connecting kits, XY linking kit



Pull handle, Aluminium



Security pull handle, Thermoplastic



Sealing washer Hygienic Usit®, Stainless steel - Black EPDM



Small lobed handle, Polyamide



Worm and wheel set, Hardened steel



Invisible hinge, Invisible - 90° opening



Right angled gearbox, from 19 to 70 Nm



Sealing strip, Clipping



Right angle helical reducers, from 0.40 to 2.53 Nm

Complementary products



Magnetic stud with central hole, With central hole



Magnetic stud with threaded hole, With threaded hole