

AlNico

- AINiCo magnets with central through drilled mounting hole
- Both faces are machine finished and have a strong attraction force in a reduced size
- Working temperature -50°C to +450°C
- Good shock resistance

For recessed mounting, following precautions should be observed


- in a non-ferrous support: none specified
- in a ferrous support: magnet should be isolated from the support by an air gap or non-ferrous material

Applications

- Suitable for fixing or positioning of components in reduced spaces and possibly subject to high temperatures
- Positioning of inserts in moulding machines...







DISCOUNTS

Qty	1+	6+	20+	40+	60+
Disc.	List	-15%	-20%	-30%	On request

Part numbe	r ØD	Ød	E	F (daN)	Weight (g)	Stock*	Price each 1 to 5
VAP19-8	19	3,5	8,0	3,0	18	~	6,65 €
VAP28-9	29	5,0	9,0	5,0	46	~	10,62 €
VAP38-11	38	5,0	10,5	9,5	97	-	15,71 €

^{*}Depending on availability - Dimensions in mm

Our other products



Worm and wheel set, Machined plastic (delrin)



Worm and wheel set, Non hardened steel



Cylindrical threaded sleeve, Cylindrical stainless steel



Internal epicyclic servo reducers, from 210 to 380 Nm



Connecting plate for T type timing belts, T5



Adjustable cell support, Adjustable



Cylindrical roller thrust bearing, Steel



Automatic chain tensioner, With stainless steel sprocket



Reducing sleeve for OP indicators, Reduction socket



Sealed flange bearing unit for Food Industry, cover



Tools Hygienic Usit® and Hygienic Design®, Protective



Internal gear, Machined plastic (delrin)

Complementary products



Magnetic stud with central hole, With central hole



Magnetic stud with threaded hole, With threaded hole